



About Us

MeiG Smart Technology Co., Ltd (Stock Code:002881) was established in 2007, headquartered in Shenzhen, Guangdong Province. As a world-class provider of IoT terminals and wireless data solutions, MeiG works hard to be an R&D-driven enterprise, and has a team of nearly 1,000 employed in Shenzhen, Shanghai and Xi'an R&D centers.

Based on advanced 4G & 5G wireless communication technology and IoT industry, MeiG Smart focuses on providing standardized and intelligent communication modules, IoT solutions, technology development service and systematic solutions for cloud platform with MeiGLink brand at the core for global customers. MeiG is taking the lead in many IoT core applications, and has IoT customers spreading over 100 countries and regions around the world.

Adhering to the business philosophy of "integrity, responsibility, innovation and sharing", MeiG Smart will continue to rely on forward-looking wireless communication technology and high-quality smart IoT products to create value for global customers. Facing a future world of intelligent connectivity, MeiG will focus on such core technologies as 5G, IoT, and AI to make continuous progress as a leading enterprise in the IoT industry.



Shenzhen Headquarters/R&D Center



Shanghai R&D Center



Xi'an R&D Center



Nantong R&D Center

Two Driving Forces: Module+Solution

Leading Technology: Intelligence+Customization

Capability Architecture: Software+Hardware+Manufacturing

Smart Module Shipments Ranked First in China for 3 Years in a Row

The First to Launch AI Computing Modules in the Industry

The First to Run Stable Diffusion on AI Computing Modules


100 Tops AI Computing Modules: Accelerating Edge AI Deployment

Winning Bidder for China Unicom's 5G Smart Module and Cat.1 Module

Global Cooperation with Tier1 and ICT Customers

5G Smart Cockpit Module Leads The Market

Operation Principle



Our Advantage



Edge AI

Industry's First High-Performance AI Module
First in Industry to Run Stable Diffusion Model
Launch of **100Tops Flagship** AI Module
Support Deepseek, Llama, 100+ AI models




R&D Driven

1000+ R&D teams
500+ patents
5G+Wi-Fi 7+Android(Windows, Linux)
Edge & Hybrid AI with Strong R&D



Developing Momentum


30% IoT business growth
50% Auto business growth
100% AI Module growth
Leading AI Module Development



Delivery Capacity

Global technical support
multi-brand delivery
2 Domestic Factories (Hangzhou & Shenzhen)
2 Overseas EMS Factories (Vietnam & Japan)

Global Distribution



Module Portfolio



5G SoC

 SRM6690 <ul style="list-style-type: none"> • QCM6690 • 8-Cores up to 2.9Ghz • 5G NR Sub-6GHz • Android 15 • Wi-Fi 7 • L1+L5 GPS • LGA • 55.0*45.0*2.8mm 	 SRM955 <ul style="list-style-type: none"> • QCM6490 • 8-Cores 2.7Ghz • Android • Wi-Fi 6E • LGA • 55.0x45.0x3.95mm 	 SRM930/L <ul style="list-style-type: none"> • QCM6490/5430 • 8-Cores up to 2.7Ghz • 5G NR Sub-6GHz • Android/Ubuntu • Wi-Fi 6E • L1+L5 GPS • LGA • 47.0*48.0*3.0mm 	 SRM700 <ul style="list-style-type: none"> • QCM4490 • 8-Cores up to 2.4Ghz • 5G NR Sub-6GHz • Android • Wi-Fi 6E • L1+L5 GPS • LGA • 47.0*48.0*3.0mm 	 SRM900/L <ul style="list-style-type: none"> • SM6350/SM4350 • 8-Cores 2.0Ghz • Android • Wi-Fi ax ready • LGA • 47.0x48.0x3.0mm
---	--	--	--	---

5G M2M

 SRM819W <ul style="list-style-type: none"> • X85 • 3GPP Release 18 • 5G NR SA & NSA • LTE Cat.20 • LGA • 56.0*53.0*2.95mm 	 SRM812 <ul style="list-style-type: none"> • V620 • 3GPP Release 16 • 5G NR SA & NSA • LTE Cat.20 • LGA • 45.0*45.0*3.6mm(TBD) 	 SRM817M <ul style="list-style-type: none"> • X72 • 3GPP Release 17 • 5G NR SA & NSA • LTE Cat.20 • LGA • 56.0*53.0*2.95mm 	 SRM825N <ul style="list-style-type: none"> • X62 • 3GPP Release 16 • 5G NR SA & NSA • LTE Cat.19 • M.2 • 30.0*52.0*2.3mm 	 SRM815NL <ul style="list-style-type: none"> • X62 • 3GPP Release 16 • 5G NR SA&NSA • LTE Cat.19 • LGA • 46.0*56.0*4.3mm
 SRM815 <ul style="list-style-type: none"> • X55 • 3GPP Release 15 • 5G NR SA & NSA • LTE Cat.20 • LGA • 44.0*41.0*2.8mm 	 SRM810 <ul style="list-style-type: none"> • V510/V516 • 3GPP Release 15 • 5G NR SA&NSA • LTE Cat.12 • LGA • 30.0*41.0*2.7mm 	 SRM821 <ul style="list-style-type: none"> • V510/V516 • 3GPP Release 15/16 • 5G NR SA & NSA • LTE Cat.12 • M.2 • 30.0*52.0*2.3mm 	 SRM813Q <ul style="list-style-type: none"> • X35 • 3GPP Release 17 • 5G RedCap • LTE Cat.4 • LGA • 29.0*32.0*2.4mm 	 SRM813A <ul style="list-style-type: none"> • ASR1903 • 3GPP Release 17 • 5G RedCap • LTE Cat.4 • LGA • 29.0*32.0*2.7mm

AI

 SNM980 <ul style="list-style-type: none"> • Q-8750 • Wi-Fi 7 • BT6.0 • Android • ~61 TOPS(int8) • LGA • 42.0*47.0*2.7mm 	 SNM970 <ul style="list-style-type: none"> • QCS8550 • Android/Linux • Wi-Fi 7 • ~48 TOPs • LGA • 40.0x45.5x2.7mm 	 SNM960 <ul style="list-style-type: none"> • SM8475 • Android • Wi-Fi 6E • ~27 TOPs • LGA • 40.0x45.5x2.7mm 	 SNM950 <ul style="list-style-type: none"> • QCS8250 • Android/Linux • Wi-Fi 6E • ~15 TOPs • LGA • 40.0x45.5x2.7mm 	 SNM930/930L <ul style="list-style-type: none"> • QCS6490/QCS5430 • Android/Linux • Wi-Fi 6E • ~12 TOPs • LGA • 47.0x48.0x3.0mm
 SNM900 <ul style="list-style-type: none"> • SM6350 • Android • Wi-Fi ax ready • ~2.4 TOPs • LGA • 47.0x48.0x3.0mm 	 SNM920 <ul style="list-style-type: none"> • QCS6125 • Android • 2.4G/5G • ~0.2 TOPs • LCC+LGA • 41.0x45.5x2.85mm 	 SNM972 <ul style="list-style-type: none"> • QCS8550 • Android/Linux • ~48 TOPs • PCIe • 47.0x64.0x6.3mm 	 SNM962 <ul style="list-style-type: none"> • SM8475 • Android • ~27 TOPs • PCIe • 47.0x64.0x6.3mm 	 SNM952 <ul style="list-style-type: none"> • QCS8250 • Android/Linux • ~15 TOPs • PCIe • 47.0x64.0x6.3mm

4G SoC

 SLM927 <ul style="list-style-type: none"> • QCM6225 • 8-Cores 2.4Ghz • Android • Wi-Fi ax ready • LCC+LGA • 41.0x41.0x2.6mm 	 SLM927M <ul style="list-style-type: none"> • SM4250 • 8-Cores 1.6Ghz • Android • Wi-Fi ax ready • LCC+LGA • 41.0x41.0x2.6mm 	 SLM926 <ul style="list-style-type: none"> • QCM4290 • 8-Cores 2.0Ghz • Android • Wi-Fi 5 • LCC+LGA • 41.0x45.5x3.0mm 	 SLM920 <ul style="list-style-type: none"> • QCM6125 • 8-Cores 2.0Ghz • Android • Wi-Fi 5 • LCC+LGA • 41.0x45.5x3.0mm 	 SLM900 <ul style="list-style-type: none"> • SDM660 • 8-Cores 2.2Ghz • Android • Wi-Fi 5 • LCC+LGA • 41.0x45.5x3.0mm
 SLM759 <ul style="list-style-type: none"> • SDM450/MSM8953 • 8-Cores 2.0Ghz • Android • Wi-Fi 5 • LCC+LGA • 43.0x44.0x2.85mm 	 SLM758 <ul style="list-style-type: none"> • SDM450/MSM8953 • 8-Cores 2.0Ghz • Android • Wi-Fi 5 • LCC+LGA • 41.0x45.5x2.85mm 	 SLM757 <ul style="list-style-type: none"> • MSM8917 • 4-Cores 1.4Ghz • Android • Wi-Fi 5 • LCC+LGA • 41.0x41.0x3.0mm 	 SLM756 <ul style="list-style-type: none"> • MSM8909 • 4-Cores 1.1Ghz • Android • Wi-Fi 5 • LCC+LGA • 39.0x44.0x3.0mm 	 SLM755L <ul style="list-style-type: none"> • MSM8909 • 4-Cores 1.1Ghz • Android • Wi-Fi 5 • LCC+LGA • 40.5x40.5x2.85mm
 SLM550 <ul style="list-style-type: none"> • QCM2290 • 4-Cores 2.0Ghz • Android • Wi-Fi 5 • LCC+LGA • 40.5x40.5x2.85mm 	 SLM550S <ul style="list-style-type: none"> • 8581E • 8-Cores 1.6Ghz • Android • Wi-Fi 5 • LCC+LGA • 40.5x40.5x2.85mm 	 SLM500Q <ul style="list-style-type: none"> • QCM2150 • 4-Cores 1.3Ghz • Android • Wi-Fi 5 • LCC+LGA • 40.5x40.5x2.85mm 	 SLM500L <ul style="list-style-type: none"> • SDM450 • 8-Cores 1.8Ghz • Android • Wi-Fi 5 • LCC+LGA • 40.5x40.5x2.85mm 	 SLM500S <ul style="list-style-type: none"> • 8541E • 4-Cores 1.4Ghz • Android • Wi-Fi 5 • LCC+LGA • 40.5x40.5x2.85mm

Automotive Telematics

 MA925 <ul style="list-style-type: none"> • SA525M • 22K DMIPS CPU • 5G R16+V2X • LGA • 54.5*53.0*3.45mm 	 MA922 <ul style="list-style-type: none"> • SA522M • 20K DMIPS CPU • 5G R16+V2X • LGA • 54.5*53.0*3.45mm 	 MA912 <ul style="list-style-type: none"> • SA522M • 20K DMIPS CPU • 5G R16+V2X • LGA • 48.0*48.0*3.45mm 	 MA800/A <ul style="list-style-type: none"> • MDM9628/ASR1806 • 2-Cores 1.2/1.5Ghz • LTE Cat.4 • LGA • 37.5*33.0*3.0mm 	 MA710A <ul style="list-style-type: none"> • ASR1903 • 5G RedCap • LTE Cat.4 • LGA • 37.5*33.0*3.0mm
--	--	--	--	--

Module Portfolio

Automotive Cockpit

SRM965

- QCM8538
- 8-Cores up to 3.2GHz
- 5G NR Sub-6GHz
- Android
- Wi-Fi 7
- L1+L5 GPS
- SIP
- 62.0*62.0*4.5mm

SLM925

- QCM6125
- 8-Cores 2.0GHz
- LTE Cat.6
- Android
- Wi-Fi 5
- LGA
- 43.0*44.0*2.85mm

SRM930

- QCM6490
- 8-Cores up to 2.7GHz
- 5G NR Sub-6GHz
- Android/Windows/Ubuntu
- Wi-Fi 6E
- L1+L5 GPS
- LGA
- 47.0*48.0*3.0mm

MA951

- SA8155P
- Dual DDR
- AEC-Q104
- QNX+Android
- BGM970
- 50.0*52.0*4.51mm

SRM935U

- UIS7870
- 8-Cores up to 2.7GHz
- 5G NR Sub-6GHz
- Android
- Wi-Fi 5
- LGA
- 50.0*50.0*3.6mm

LTE-A

SLM828

- SDX12
- LTE Cat.6
- Mini PCIe
- 51.0x30.0x4.5mm

SLM828M

- SDX12
- LTE Cat.6/12
- M.2
- 42.0x30.0x2.3mm

SLM828G

- SDX12
- LTE Cat.6/12
- LGA
- 39.5x37.0x3.0mm

SLM828A

- ASR1828
- LTE Cat.6
- LGA
- 39.5x37.0x3.0mm

LTE

SLM720

- MDM9X07
- LTE Cat.4
- M.2
- 42.0x30.0x2.3mm

SLM750

- MDM9X07
- LTE Cat.4
- LCC
- 29.0x32.0x2.8mm

SLM750

- MDM9X07
- LTE Cat.4
- Mini PCIe
- 51.0x30.0x4.8mm

SLM770A

- ASR1803
- LTE Cat.4
- LCC
- 29.0x32.0x2.4mm

SLM770A

- ASR1803
- LTE Cat.4
- Mini PCIe
- 51.0x30.0x4.8mm

SLM770U

- V8310
- LTE Cat.4
- LCC
- 29.0x32.0x2.4mm

SLM770U

- V8310
- LTE Cat.4
- Mini PCIe
- 51.0x30.0x4.8mm

Cat.1

SLM310

- 8910DM
- LTE Cat.1 & GSM & GNSS
- LCC+LGA
- 28.0*31.0*2.4mm

SLM320

- 8910DM
- LTE Cat.1 & GSM & GNSS
- Mini PCIe
- 29.0*32.0*2.4mm

SLM320

- 8910DM
- LTE Cat.1 & GSM & GNSS
- Mini PCIe
- 51.0*30.0*5.0mm

SLM322

- 8910DM
- LTE Cat.1 & GSM
- LCC+LGA
- 22.9*23.9*2.4mm

SLM326

- 8910DM
- LTE Cat.1 & GSM
- LGA
- 27.6*25.4*2.3mm

SLM336E

- 8910DM
- LTE Cat.1
- LGA
- 19.9*23.6*2.4mm

SLM336Q

- QCX216
- LTE Cat.1
- LGA
- 19.9*23.6*2.4mm

SLM750-Z

- MDM9207-1
- LTE Cat.1
- LCC
- 29.0*32.0*2.8mm

SLM750-Z

- MDM9207-1
- LTE Cat.1
- Mini PCIe
- 51.0*30.0*4.8mm

Cat.M

SLM156

- MDM9205
- NB-IoT/Cat.M/GPRS
- LCC
- 20.0*21.0*2.3mm

SLM156H

- MDM9205
- NB-IoT/Cat.M
- LCC
- 20.0*21.0*2.3mm

SLM156N

- MDM9205
- NB-IoT/Cat.M/GPRS
- LGA
- 23.6*19.9*2.3mm

NB-IoT

SLM130-G

- XY1100S
- LTE Cat.NB-B3/B5/B8/B20/B28
- LCC
- 17.7*15.8*2.0mm

SLM130E

- EC826
- LTE Cat.NB-B3/B5/B8/B20/B28
- LCC+LGA
- 17.7*15.8*2.0mm

SLM130-NA-S

- XY1200S
- Default: B1/B5/B8/B3/B18/B20/B28/B26
- Optional: B2/B4/B12/B13/B66/B5/B26/B71
- GNSS
- LCC
- 17.7*15.8*2.0mm

SLM190T

- XY3100E
- Default: B2/B4/B12/B13/B66/B5/B26/B71
- Optional: B1/B5/B8/B3/B18/B20/B28/B26
- GNSS+Wi-Fi Scan
- LCC
- 19.9*23.6*2.2mm


GNSS

SGM308

- AG3352
- L1
- LCC
- 10.1*9.7*2.4mm

SGM308I

- CC1167Q
- L1
- LCC
- 10.1*9.7*2.4mm






MeiG Smart 5G SoC Module Series



Product	SRM6690	SRM955	SRM930	SRM700
Product Picture				
OS	Android	Android	Android/Windows/Ubuntu	Android
CPU	Octa-core	Octa-core	Octa-core	Octa-core
Memory	64+4/128+8(GB)	128+8/256+12(GB)	64+4/128+8(GB)	64+4/128+6(GB)
Band(MHz)	<p>-US</p> <p>5G-FDD N2/N5/N7/N12/N13/N14/N25/N28/N30/N66/N71 5G-TDD N30/N41/N43/N77/N78 5G 2*2 MIMO (UL/N30/N41/N43/N77/N78 5G 4*4 MIMO (DL/N2/N7/N25/N30/N66/N71/N13/N14/N25/N28/N30/N66/N71/N77/N78 4G-FDD B2/B4/B5/B7/B12/B13/B14/B17/B25/B26/B29/B30/B66/B71 4G-TDD B38/B41/B64 4G 4*4 MIMO (DL) B2/B4/B5/B7/B25/B30/B38/B41/B42/B43/B44/B46/B66 4G 2*2 MIMO (DL) B5/B12/B13/B14/B17/B29/B71 WCDMA B2/B4/B5 GSM B2/B3/B5/B8</p> <p>-EMEA</p> <p>5G-FDD N1/N2/N3/N5/N7/N8/N28/N28 5G-TDD N30/N41/N43/N77/N78/N79 5G 2*2 MIMO (UL/N1/N2/N3/N5/N7/N8/N28/N28 5G 4*4 MIMO (DL/N1/N2/N3/N5/N7/N8/N28/N28/N79 4G-FDD B1/B2/B3/B4/B5/B7/B8/B20/B26/B28 4G-TDD B38/B41/B64/B43 4G 4*4 MIMO (DL) B1/B2/B3/B4/B5/B7/B8/B20/B26/B28/B38/B41/B42/B43 4G 2*2 MIMO (DL) B2/B3/B4/B5/B7/B8/B20/B26/B28/B38/B41/B42/B43 WCDMA B1/B2/B5/B8 GSM B2/B3/B5/B8</p>	<p>-US</p> <p>5G-NR-N2/N5/N12/N25/N30/N38/N41 N48/N66/N71/N77/N78 LTE-FDD B2/B4/B5/B7/B12/B13/B14 B17/B25/B29/B30/B46/B66/B71 LTE-TDD B38/B41/B42/B43/B48 WCDMA B2/B4/B5 GSM B2/B3/B5/B8</p> <p>-EMEA</p> <p>5G-NR-N1/N3/N7/N8/N28/N38/N41 N77/N78/N79 LTE-FDD B1/B2/B3/B5/B7/B8/B20 B26/B28 LTE-TDD B38/B40/B41 WCDMA B1/B2/B5/B8 GSM B2/B3/B5/B8</p>	<p>-C</p> <p>5G-NR-N1/N3/N28/N41/N78/N79 LTE-FDD B1/B3/B5/B7/B8/B20/B28 LTE-TDD B34/B39/B40/B41 WCDMA B1/B5/B8 GSM B2/B3/B5/B8</p> <p>-E</p> <p>5G-FDD N1/N2/N3/N5/N7/N8/N28 5G-TDD N30/N41/N43/N77/N78/N79 4G-FDD B1/B2/B3/B4/B5/B7/B8/B20/B26/B28 4G-TDD B38/B41/B64 4G 4*4 MIMO (DL) B1/B2/B3/B4/B5/B7/B8/B20/B26/B28/B38/B41/B42/B43 4G 2*2 MIMO (DL) B5/B12/B13/B14/B17/B29/B71 WCDMA B1/B5/B8 GSM B2/B3/B5/B8</p> <p>-A</p> <p>5G-FDD N2/N5/N7/N8/N12/N13/N14/N25/N28/N66/N71 5G-TDD N30/N41/N43/N77/N78/N79 4G-FDD B1/B2/B3/B4/B5/B7/B8/B20/B26/B28 4G-TDD B38/B41/B64 4G 4*4 MIMO (DL) B1/B2/B3/B4/B5/B7/B8/B20/B26/B28/B38/B41/B42/B43 4G 2*2 MIMO (DL) B5/B12/B13/B14/B17/B29/B71 WCDMA B1/B5/B8 GSM B2/B3/B5/B8</p> <p>-L</p> <p>5G-FDD N1/N2/N3/N5/N7/N8/N28/N28 5G-TDD N30/N41/N43/N77/N78/N79 4G-FDD B1/B2/B3/B4/B5/B7/B8/B20/B26/B28 4G-TDD B38/B41/B64 4G 4*4 MIMO (DL) B1/B2/B3/B4/B5/B7/B8/B20/B26/B28/B38/B41/B42/B43 4G 2*2 MIMO (DL) B5/B12/B13/B14/B17/B29/B71 WCDMA B1/B5/B8 GSM B2/B3/B5/B8</p> <p>-J</p> <p>5G-FDD N1/N2/N3/N5/N7/N8/N28 5G-TDD N30/N41/N43/N77/N78/N79 4G-FDD B1/B2/B3/B4/B5/B7/B8/B20/B26/B28 4G-TDD B38/B41/B64 4G 4*4 MIMO (DL) B1/B2/B3/B4/B5/B7/B8/B20/B26/B28/B38/B41/B42/B43 4G 2*2 MIMO (DL) B5/B12/B13/B14/B17/B29/B71 WCDMA B1/B5/B8 GSM B2/B3/B5/B8</p>	
Package	LGA	LGA	LGA	LGA:458Pin
Dimension(mm)	55.0*45.0*2.8	55.0*45.0*3.95	47.0*48.0*3.0	47.0x48.0x3.0
5G	5G	5G	5G	5G
Supply Voltage	3.5V~4.35V, typ.3.8V	3.5V~4.35V, typ.3.8V	3.5V~4.35V, typ.3.8V	3.5V~4.2V, typ.3.8V
Working Temperature	-30°C~+75°C	-30°C~+75°C	-30°C~+75°C	-30°C~+75°C
Storage Temperature	-40°C~+85°C	-40°C~+85°C	-40°C~+85°C	-40°C~+90°C
Data Transmission				
5G NR Speed	5G:DL 2.5Gbps/UL 660Mbps	5G:DL 2.5Gbps/UL 660Mbps	5G:DL 2.5Gbps/UL 660Mbps	5G:DL 2.5Gbps/UL 660Mbps
LTE Speed(Mbps)	LTE:DL 800Mbps/UL 210Mbps	LTE:Max 150(DL)/50(UL)	LTE:Max 150(DL)/50(UL)	LTE:DL 800Mbps/UL 210Mbps
DC-HSPA+Speed(Mbps)	Max 42(DL)/Max 11(UL)	Max 42(DL)/Max 11(UL)	Max 42(DL)/Max 11(UL)	Max 42(DL)/Max 11(UL)
WCDMA Speed(Kbps)	Max 384(DL)/Max 384(UL)	Max 384(DL)/Max 384(UL)	Max 384(DL)/Max 384(UL)	Max 384(DL)/Max 384(UL)
TD-SCDMA Speed(Mbps)	Max 4.2(DL)/Max 2.2(UL)	Max 4.2(DL)/Max 2.2(UL)	Max 4.2(DL)/Max 2.2(UL)	Max 4.2(DL)/Max 2.2(UL)
EDGE Speed(Kbps)	•	•	•	•
GPRS Speed(Kbps)	•	•	•	•
SMS	•	•	•	•
CSD	•	•	•	•
Special Function				
Firmware Upgrade	Upgrade through USB interface	Upgrade through USB interface	Upgrade through USB interface	Upgrade through USB interface
VoLTE	•	•	•	•
WLAN	Wi-Fi(2 × 2 MU-MIMO 802.11a/b/g/n/ac/ax/be)	Wi-Fi 6E(2 × 2 MU-MIMO 802.11a/b/g/n/ac/ax)	Wi-Fi 6E(2 × 2 MU-MIMO 802.11a/b/g/n/ac/ax)	Wi-Fi 6E(2 × 2 MU-MIMO 802.11a/b/g/n/ac/ax)
BT	BT5.4	BT5.2	BT5.2	BT5.2
FM	—	—	—	—
GNSS	Gen 9v5.2:GPS/GLONASS/NavIC BeiDou/Galileo/QZSS/SBAS	GPS/Beidou/Glonass/Galileo,L1+L5 GPS	GPS/Beidou/Glonass/Galileo,L1+L5 GPS	GPS/Beidou/Glonass/Galileo,L1+L5 GPS
Interface				
Display	1×4-lane DSI, 4K30 DisplayPort 1.4 (eUSB 2.0 + DisplayPort concurrency) DP SST-1 × 4K60 DP MST-2 × 4K30	FHD+@60fps MIPI-DSI + 4K@60fps Displayport One 4-lane DSI, D-PHY 1.2 or C-PHY 1.2 DisplayPort v1.4 over USB Type-C	MIPI DSI FHD + 1200*2520@144Hz Display Port: 3840 × 2160@60Hz 3840 × 2160@60Hz	FHD+(1080x2520)@ 60/90/120 Hz One 4-lane DSI
Camera	4 × 4-lane CSI 21 + 21 + 21 MP or 64MP 30fps	5 × 4-lane CSI D-PHY 1.2 or C-PHY 1.2 3 × 14 bit ISP + 2 × lite ISP 22 + 22 + 22 MP or 64MP 30fps	5x4-lane CSI D-PHY 1.2 or C-PHY 1.2 3x14 bit ISP + 2x lite ISP 22+22+22MP or 64MP 30fps	3x4-lane CSI D-PHY 1.2 or C-PHY 1.2 16+16MP or 25MP@30fps
Video	Encode:4K@60fps H.264/HEVC/VP9 Decode:4K@120fps H.264/HEVC/VP9 Concurrency:UHD30 decode + UHD30 encode	Encode: 4K@30fps H.264/H.265 Decode: 4K@60fps H.264/H.265/VP9 Concurrency: 1080P@60fps decode + 1080P@60fps encode	Encode: 4K@30fps H.264/H.265 Decode: 4K@60fps H.264/H.265/VP9 Concurrency: 1080P@60fps decode + 1080P@60fps encode	Encode: 1080P@30fps H.264/H.265 Decode: 1080P@60fps H.264/H.265/VP9 Concurrency: 1080P@30fps decode + 1080P@30fps encode
Audio	Analog output:speakers,earphones, headphone;4*DMICs Analog input;4 × MIS ports, 2x I2S ports Supports Audio over USB Type-C	Analog output:speakers,earphones, headphone;3*DMICs Analog input; 2x I2S ports Supports Audio over USB Type-C	Mp3:AAC+eAAC;AMR-NB, -WB,G.711,WMA 9/10 Pro	MP3;aacPlus,eAAC;ARM-NB,AMR-WB, G.711,Windows Media Audio(WMA)9/10 Pro
Hardware Interface	1 × USB 3.1 Gen1, USB 2.0 Supports OTG UART*3 I2C*10 SPI*2 ADC*2 GPIO*13 USIM*2 SDIO*1	1 × USB 3.1 Gen1, USB 2.0 Supports OTG UART*3 I2C*10 SPI*2 ADC*8 GPIO*19 USIM*2 SDIO*1	UART*3 I2C*5 SPI*2 ADC*2 GPIO*19 USIM*2 SDIO*1	USB 3.1 *1, USB2.0*1, Supports OTG UART*3 I2C*8 SPI*2 ADC*2 GPIO*76 USIM*2 SDIO*1
Antenna	Main antenna, diversity antenna, GNSS	Main antenna, diversity antenna, GNSS	Main antenna, diversity antenna, GNSS	Main antenna, diversity antenna, GNSS antenna, Wi-Fi/BT antenna
Certifications				
Certifications	CCC/CE*/FCC*/IC*	FCC/CE/IC/RGCM/JKCA/PTCRB/GCF(US SKU) AT&T/Verizon*/T-Mobile*	CCC/CE*/GTA*	CCC*/CE*/FCC*/IC*/JATE*
Recommended Applications				
Application Fields	Smart POS, Security Monitoring, Automotive Device, VR/AR, Information Collection equipment, Smart Robots, Smart Homes, Intelligent Hardware, Industrial Smart Handhelds, Smart PAD, UAV, VR Camera, Full-view Camera, Multi-touch Device, Walkie-talkie, Smart Wearables, Vending Machines, Logistics Cabinet etc.			




MeiG 5G M2M Module Series

5G

Product	SRM819W	SRM812	SRM817M
Product Picture			
Package	LGA	LGA	LGA:537-Pin
Dimension(mm)	56.0*53.0*2.95	45.0*53.0*2.7(TBD)	56.0x53.0x2.95
5G NR Technical Standard	3GPP Release 18, mmWave&Sub-6GHz, NSA/SA mode	3GPP Release 16, Sub-6GHz, NSA/SA mode	3GPP Release 17, Sub-6GHz, NSA/SA mode
Band(MHz)	-EA 5G NR mmWave: N257/258/259 5G Sub6G: FDD: N1/N3/N5/N7/N8/N20/N28/N71/N75/N76 TDD: N38/N40/N41/N77/N78 LTE-FDD: B1/B3/B5/B7/B8/B20/B28/B32/B71 LTE-TDD: B38/B40/B41/B42/B43	-EA 5G SA&NSA: n1/3/5/7/8/20/28/38/40/41/71/77/78/79* LTE-FDD: B1/3/5/7/8/20/28/32 LTE-TDD: B34/38/39/40/41/42/43 WCDMA: B1/5/8	-EA 5G SA&NSA: FDD: N1/N3/N5/N7/N8/N20/N28/N71/N75/N76 TDD: N38/N40/N41/N77/N78 LTE-FDD: B1/B3/B5/B7/B8/B20/B28/B32 LTE-TDD: B38/B40/B41/B42/B43/B71 WCDMA: B1/B5/B8
	-NA 5G NR mmWave: N259/260/261 5G Sub6G: FDD: N2/N5/N7(30)/N12/N13/N14/N25/N26/N29/N66/N71 TDD: N38/N41/N48/N77/N78 LTE-FDD: B2/B4/B5/B7(30)/B12/B13/B14/B17/B25/B26/B66/B71 LTE-TDD: B38/B41/B42/B43/B48		-NA 5G SA&NSA: FDD: N2/N5/N7(30)/N12/N13/N14/N25/N26/N29/N66/N71 TDD: N38/N41/N48/N77/N78 LTE-FDD: B2/B4/B5/B7(30)/B12/B13/B14/B17/B25/B26/B66/B71 LTE-TDD: B38/B41/B42/B43/B48 WCDMA: B2/B4/B5
Modulation type	DL: QPSK, 16QAM, 64QAM and 256QAM UL: BPSK, QPSK, 16QAM, 64QAM and 256QAM	DL: QPSK, 16QAM, 64QAM and 256QAM UL: BPSK, QPSK, 16QAM, 64QAM	DL: QPSK, 16QAM, 64QAM and 256QAM UL: BPSK, QPSK, 16QAM, 64QAM and 256QAM
Sub-Carrier Spacing(SCS)	SCS support 15KHz and 30KHz	SCS support 15KHz and 30KHz	SCS support 15KHz and 30KHz
5G DL 4x4 MIMO Band	-EA: N1/3/7/38/40/41/77/78 -NA: N2/25/7(30)/38/41/66/77/78	n1/3/7/38/40/41/77/78/79*	-EA: N1/N3/N7/N38/N40/N41/N77/N78 -NA: N2/N7/N38/N40/N41/N66/N77/N78
5G UL 2x2 MIMO Band	-EA: N1/3/7/38/40/41/77/78 -NA: N2/25/7(30)/38/41/77/78	n38/40/41/77/78/79*	-EA: N38/N40/N41/N77/N78 -NA: N38/N41/N77/N78
Weight	<20g	<12g	<15g
Working Temperature	Normal operating temperature: -10°C to +55°C	Normal operating temperature: -30°C ~ +75°C Extended operating temperature: -40°C ~ +85°C	Normal operating temperature: -30°C ~ +75°C Extended operating temperature: -40°C ~ +85°C
Data Transmission			
5G NR Speed	Downlink up to 11Gbps -Uplink up to 3.7Gbps	Downlink up to 4.67Gbps -Uplink up to 1.875Mbps	Sub6G: -Downlink up to 4Gbps -Uplink up to 900Mbps
LTE Speed(Mbps)	-Downlink up to 2Gbps -Uplink up to 200Mbps	-Downlink up to 1.6Gbps -Uplink up to 200Mbps	-Downlink up to 2Gbps -Uplink up to 200Mbps
WCDMA Speed(Kbps)	-Downlink up to 42.4Mbps -Uplink up to 5.76Mbps	-Downlink up to 42.4Mbps -Uplink up to 5.76Mbps	-Downlink up to 42.4Mbps -Uplink up to 5.76Mbps
Interface			
SIM	1.8V/3V x2	1.8V/3V x2	1.8V/3V x2
eSIM	•	-	•
UART	•	•	•
USB	USB 3.1	USB 3.1 x1 USB2.0 x1	USB 3.1
PCIe	PCIe 3.0 x3	PCIe 3.0 x2	PCIe 3.0 x3
RGMII	USXGMII x2	RGMII x1 or SGMII/USXGMII x1	USXGMII x2
I2C	•	•	•
PCM Voice	•	•	•
ADC	•	•	•
GPIO	•	•	•
Antenna	mmWave RF Connector : x8 ANT_PRI/ANT_DIV/ANT_MIMO: x6 8RX : x4 GNSS: x1	total 8: ANT_PRI/ANT_DIV/ANT_MIMO: x6 LB+LB: x2	ANT_PRI/ANT_DIV/ANT_MIMO: x6 GNSS: x1
Special Function			
TTS	*	*	*
TCP/IP	•	•	•
FTP	*	*	*
HTTP	*	*	*
RIL Driver	Android 4.2/4.4/5.0/5.1/6.0/7.0/8.0/9.0/10.0	Android 4.2/4.4/5.0/5.1/6.0/7.0/8.0/9.0/10.0	Android 4.2/4.4/5.0/5.1/6.0/7.0/8.0/9.0/10.0
NDIS	Windows 7/8/10/11	Windows 7/8/10/11	Windows 7/8/10/11
ECM	•	•	•
Gobinet	Linux 2.6 or later	-	Linux 2.6 or later
GNSS	•	-	•
USB Audio Class (UAC)	*	*	*
IP Passthrough	•	*	•
Firmware Update	USB/DFOTA	USB/DFOTA	USB/DFOTA
Electrical Parameter			
Supply Voltage	3.15V~4.35V, typical 3.8V	3.15V~4.35V, typical 3.8V	3.3V~4.35V, typ.3.8V
Sleep Power Consumption	<6mA	<10mA	<6mA
Certifications			
Certifications	CE*/FCC*	CE*	CE*/FCC*
Recommended Applications			
Application Fields	It can be widely used in CPE home gateway, TV, AR/VR, industrial router, set-top box, carrier terminal, video surveillance, industrial interconnection and other fields.		

MeiG 5G M2M Module Series

5G

Product	SRM815/SRM815-GL	SRM825	SRM825W
Product Picture			
Package	LGA:392-Pin Support M.2 & MiniPCIe adapter board adapter	M.2:75-Pin	M.2:75-Pin
Dimension(mm)	44.0x41.0x2.8 SRM815-GL:44.0x43.0x2.8	30.0x52.0x3.6	30.0x52.0x3.6
5G NR Technical Standard	3GPP Release 15, Sub-6GHz, NSA/SA mode	3GPP Release 15, Sub-6GHz, NSA/SA mode	3GPP Release 15, Sub-6GHz & mmWave, NSA/SA mode
Band(MHz)	-EA 5G SA:N1/N3/N28/N40/N41/N77/N78/N79 5G NSA:N41/N77/N78/N79 LTE-FDD:B1/B3/B5/B7/B8/B18/B19/B20/B28 LTE-TDD:B34/B38/B39/B40/B41/B42 WCDMA:B1/B3/B5/B8 -CN 5G SA:N1/N28/N41/N78/N79 5G NSA:N41/N78/N79 LTE-FDD:B1/B3/B5/B8/B28 LTE-TDD:B34/B38/B39/B40/B41 WCDMA:B1/B5 -GL 5G NR Sub-6G:N1/N3/N5/N7/N8/N20/N28/N38/N40/ N41/N77/N78/N79 LTE-FDD:B1/B3/B5/B7/B8/B18/B19/B20/B28/B32 LTE-TDD:B34/B38/B39/B40/B41/B42/B43 WCDMA:B1/B3/B5/B8	-EA 5G SA:N1/N3/N5/N7/N8/N20/N28/N38/N40/ N41/N77/N78/N79 5G NSA:N1/N3/N5/N7/N8/N20/N28/N38/N40/ N41/N77/N78/N79 LTE-FDD:B1/B3/B5/B7/B8/B18/B19/B20/B28/B32 LTE-TDD:B34/B38/B39/B40/B41/B42 WCDMA:B1/B3/B5/B8 -EU 5G SA:N1/N3/N5/N7/N8/N20/N28/N38/N40/N41/ N77/N78/N79 5G NSA:N1/N3/N5/N7/N8/N20/N28/N38/N40/N41/ N77/N78/N79 LTE-FDD:B1/B3/B5/B7/B8/B18/B19/B20/B28/B32 LTE-TDD:B34/B38/B39/B40/B41/B42 WCDMA:B1/B3/B5/B8	-EA 5G SA:N1/N3/N5/N7/N8/N20/N28/N38/N40/ N41/N77/N78/N79 5G NSA:N1/N3/N5/N7/N8/N20/N28/N38/N40/ N41/N77/N78/N79 LTE-FDD:B1/B3/B5/B7/B8/B18/B19/B20/B28/B32 LTE-TDD:B34/B38/B39/B40/B41/B42 WCDMA:B1/B3/B5/B8
Modulation type	DL:QPSK, 16QAM, 64QAM and 256QAM UL: BPSK, QPSK, 16QAM, 64QAM and 256QAM	DL:QPSK, 16QAM, 64QAM and 256QAM UL: BPSK, QPSK, 16QAM, 64QAM and 256QAM	DL:QPSK, 16QAM, 64QAM and 256QAM UL: BPSK, QPSK, 16QAM, 64QAM and 256QAM
Sub-Carrier Spacing(SCS)	SCS support 15KHz and 30KHz	SCS support 15KHz and 30KHz	SCS support 15KHz and 30KHz
5G DL 4x4 MIMO Band	-EA:N1/N3/N40/N41/N77/N78/N79 -CN:N1/N41/N78/N79 -GL:N1/N3/N7/N38/N40/N41/N77/N78/N79	-EA:N1/N3/N7/N38/N40/N41/N77/N78/N79 -EU:N1/N3/N7/N38/N40/N41/N77/N78	N1/N3/N7/N38/N40/N41/N77/N78/N79
5G UL 2x2 MIMO Band	-EA:N41/N77/N78/N79 -CN:N41/N78/N79 -GL:N41/N77/N78/N79	-EA:N41/N77/N78/N79 -EU:N77/N78	N41/N77/N78/N79
Weight	<12g	<12g	<12g
Working Temperature	Normal operating temperature: -30°C ~ +75°C Extended operating temperature: -40°C ~ +85°C	Normal operating temperature: -30°C ~ +75°C Extended operating temperature: -40°C ~ +85°C	Normal operating temperature: -30°C ~ +75°C Extended operating temperature: -40°C ~ +85°C
Data Transmission			
5G NR Speed	-Downlink up to 2.1Gbps -Uplink up to 900Mbps	-Downlink up to 2.1Gbps -Uplink up to 900Mbps	-Downlink up to 2.0Gbps -Uplink up to 200Mbps
LTE Speed(Mbps)	-EA&GL:-Downlink up to 2.0Gbps -Uplink up to 200Mbps -CN:-Downlink up to 1.0Gbps -Uplink up to 150Mbps	-EA:-Downlink up to 2.0Gbps -Uplink up to 200Mbps -EU:-Downlink up to 1.0Gbps -Uplink up to 200Mbps	mmWave: -Downlink up to 6.78Gbps -Uplink up to 1.45Gbps Sub6G: -Downlink up to 2.1Gbps -Uplink up to 900Mbps
WCDMA Speed(Kbps)	-Downlink up to 42.4Mbps -Uplink up to 5.76Mbps	-Downlink up to 42.4Mbps -Uplink up to 5.76Mbps	-Downlink up to 42.4Mbps -Uplink up to 5.76Mbps
Interface			
SIM	1.8V/3V x2	1.8V/3V x2	1.8V/3V x2
eSIM	—	•	•
UART	•	•	•
USB	USB 3.1	USB 3.1	USB 3.1
PCIe	PCIe 3.0	PCIe 3.0	PCIe 3.0
RGMII	•	•	•
I2C	•	•	•
PCM Voice	•	•	•
ADC	•	•	•
GPIO	•	•	•
Antenna	total 9: ANT_PRI/ANT_DIV/ANT_MIMO: x8 GPS: x1	total 6: ANT_PRI/ANT_DIV/ANT_MIMO: x5 GPS: x1	mmWave RF connector: x8 QTM525 connector: x2 ANT_PRI/ANT_DIV/ANT_MIMO: x5 GPS: x1
Special Function			
TTS	•	•	•
TCP/IP	•	•	•
FTP	*	*	*
HTTP	*	*	*
RIL Driver	Android 4.2/4.4/5.0/5.1/6.0/7.0/8.0/9.0/10.0	Android 4.2/4.4/5.0/5.1/6.0/7.0/8.0/9.0/10.0	Android 4.2/4.4/5.0/5.1/6.0/7.0/8.0/9.0/10.0
NDIS	Windows 7/8/10	Windows 7/8/10	Windows 7/8/10
ECM	•	•	•
Gobinet	Linux 2.6 or later	Linux 2.6 or later	Linux 2.6 or later
GNSS	•	•	•
USB Audio Class (UAC)	•	•	•
IP Passthrough	•	•	•
Firmware Update	USB/DFOTA	USB/DFOTA	USB/DFOTA
Electrical Parameter			
Supply Voltage	3.3V~4.35V, typ.3.8V	3.15V~4.35V, typ.3.8V	3.15V~4.35V, typ.3.8V
Sleep Power Consumption	<6mA	<6mA	<6mA
Certifications			
Certifications	CCC/SRRC/CTA	CCC/SRRC/CTA/CE	CCC/SRRC/CTA/CE
Recommended Applications			
Application Fields	It can be widely used in CPE home gateway, TV, AR/VR, industrial router, set-top box, carrier terminal, video surveillance, industrial interconnection and other fields.		

MeiG 5G M2M Module Series



Product	SRM815N	SRM825N	SRM825WN
Product Picture			
Package	LGA:392-Pin	M.2:75-Pin	M.2:75-Pin
Dimension(mm)	44.0x43.0x2.7	30.0x52.0x2.3	30.0x52.0x2.3
5G NR Technical Standard	3GPP Release 16 , Sub-6GHz, NSA/SA mode	3GPP Release 16,Sub-6GHz, NSA/SA mode	3GPP Release 16,Sub-6GHz & mmWave, NSA/SA mode
Band(MHz)	-EA 5G SA&NSA:N1/N3/N5/N7/N8/N20/N28/N38/N40/ N41/N71/N77/N78/N79 LTE-FDD:B1/B3/B5/B7/B8/B18/B19/B20/B26/ B28/B32 LTE-TDD:B34/B38/B39/B40/B41/B42/B43 WCDMA:B1/B5/B8	-EA 5G SA&NSA:N1/N3/N5/N7/N8/N20/N28/N38/N40/ N41/N71/N77/N78/N79 LTE-FDD:B1/B3/B5/B7/B8/B18/B19/B20/B28/B32 WCDMA:B1/B5/B8 -NA 5G SA&NSA:N2/N5/N7/N12/N13/N14/N25/N38/ N41/N48/N66/N71/N77/N78 LTE-FDD:B2/B4/B5/B7/B12/B13/B14/B17/B25/B26/ B66/B71 LTE-TDD:B38/B41/B42/B43/B48 WCDMA:B2/B4/B5 -CN 5G SA:N1/N28/N41/N78/N79 5G NSA:N41/N78/N79 LTE-FDD:B1/B3/B5/B8/B28 LTE-TDD:B34/B38/B39/B40/B41 WCDMA:B1/B8	-EA 5G SA:N1/N3/N5/N7/N8/N20/N28/N38/N40/ N41/N71/N77/N78/N79 5G NSA:N1/N3/N5/N7/N8/N20/N28/N38/N40/ N41/N71/N77/N78/N257/N258 LTE-FDD:B1/B3/B5/B7/B8/B18/B19/B20/B28/B32 LTE-TDD:B34/B38/B39/B40/B41/B42 WCDMA:B1/B5/B8
Modulation type	DL:QPSK, 16QAM,64QAM and 256QAM UL:BPSK, QPSK, 16QAM,64QAM and 256QAM	DL:QPSK, 16QAM,64QAM and 256QAM UL:BPSK, QPSK, 16QAM,64QAM and 256QAM	DL:QPSK, 16QAM,64QAM and 256QAM UL:BPSK, QPSK, 16QAM,64QAM and 256QAM
Sub-Carrier Spacing(SCS)	SCS support 15KHz and 30KHz	SCS support 15KHz and 30KHz	SCS support 15KHz and 30KHz
5G DL 4x4 MIMO Band	N1/N3/N7/N38/N40/N41/N77/N78/N79	-EA:N1/N3/N7/N38/N40/N41/N77/N78/N79 -NA:N1/N3/N7/N38/N40/N41/N77/N78	N1/N3/N7/N38/N40/N41/N77/N78/N79
5G UL 2x2 MIMO Band	N38/N41/N77/N78/N79	-EA:N41/N77/N78/N79 -EU:N77/N78	N38/N41/N77/N78/N79
Weight	<12g	<8g	<8g
Working Temperature	Normal operating temperature: -30°C ~ +75°C Extended operating temperature: -40°C ~ +85°C	Normal operating temperature: -30°C ~ +75°C Extended operating temperature: -40°C ~ +85°C	Normal operating temperature: -30°C ~ +75°C Extended operating temperature: -40°C ~ +85°C
5G NR Speed	-Downlink up to 2.4Gbps -Uplink up to 900Mbps	Sub6G:-Downlink up to 2.4Gbps -Uplink up to 900Mbps	mmWave: -Downlink up to 4.3Gbps -Uplink up to 1.6Gbps Sub6G: -Downlink up to 2.3Gbps -Uplink up to 900Mbps
LTE Speed(Mbps)	-Downlink up to 1.6Gbps -Uplink up to 200Mbps	-Downlink up to 1.6Gbps -Uplink up to 200Mbps	-Downlink up to 1.6Gbps -Uplink up to 200Mbps
WCDMA Speed(Kbps)	-Downlink up to 42.4Mbps -Uplink up to 5.76Mbps	-Downlink up to 42.4Mbps -Uplink up to 5.76Mbps	-Downlink up to 42.4Mbps -Uplink up to 5.76Mbps
SIM	1.8V/3V x2	1.8V/3V x2	1.8V/3V x2
eSIM	•	•	•
UART	•	•	•
USB	USB 3.1	USB 3.1	USB 3.1
PCIe	PCIe 3.0	PCIe 3.0	PCIe 3.0
RGMII	—	—	—
I2C	•	•	•
PCM Voice	*	•	•
ADC	•	•	•
GPIO	•	•	•
Antenna	total 11: ANT_PRI/ANT_DIV/ANT_MIMO: x10 GNSS:x1	ANT_PRI/ANT_DIV/ANT_MIMO:x4 GPS:x1	mmWave RF connector:x4 ANT_PRI/ANT_DIV/ANT_MIMO:x4 GPS:x1
TTS	•	•	•
TCP/IP	•	•	•
FTP	*	*	*
HTTP	*	*	*
RIL Driver	Android 4.2/4.4/5.0/5.1/6.0/7.0/8.0/9.0/10.0	Android 4.2/4.4/5.0/5.1/6.0/7.0/8.0/9.0/10.0	Android 4.2/4.4/5.0/5.1/6.0/7.0/8.0/9.0/10.0
NDIS	Windows 7/8/10	Windows 7/8/10	Windows 7/8/10
ECM	•	•	•
Gobinet	Linux 2.6 or later	Linux 2.6 or later	Linux 2.6 or later
GNSS	•	•	•
USB Audio Class (UAC)	•	•	•
IP Passthrough	•	•	•
Firmware Update	USB/DFOTA	USB/DFOTA	USB/DFOTA
Supply Voltage	3.3V~4.35V, typ.3.8V	3.15V~4.35V, typ.3.8V	3.15V~4.35V, typ.3.8V
Sleep Power Consumption	<6mA	<6mA	<6mA
Certifications	CCC*/SRRC*/CTA*/CE*	CCC/SRRC/CTA/CE/FCC/PTCRB/GCF/JATE*/TELEC*	CCC*/SRRC*/CTA*/CE*
Recommended Applications			
Application Fields	It can be widely used in CPE home gateway, TV, AR/VR, industrial router, set-top Box, carrier terminal, video surveillance, industrial interconnection and other fields.		

MeiG 5G M2M Module Series





Product	SRM813Q	RedCap	SRM813A	RedCap
Product Picture				
Package	LGA/M.2/MiniPCIe		LGA	
Dimension(mm)	LGA: 29.0×32.0×2.4mm M.2: 30.0×42.0×3.25mm MiniPCIe: 50.95×30.0×3.45mm		29.0*32.0*2.7	
5G NR Technical Standard	3GPP Release 17, Sub-6GHz SA Only		3GPP Release 17, RedCap, Sub-6GHz SA Only	
Band(MHz)	-CN	5G NR: FDD: N1/N5/N8/N28 TDD: N41/N78 LTE-FDD: B1/B3/B5/B8 LTE-TDD: B34/B38/B39/B40/B41	-CN	5G NR: FDD: N1/N3/N5/N8/N28 TDD: N41/N78/N79 LTE-FDD: B1/B3/B5/B8 LTE-TDD: B34/B38/B39/B40/B41
	-NA	5G NR: FDD: N2/N5/N7/N12/N13/N25/N66/N71 TDD: N38/N41/N48/N77/N78 LTE-FDD: B2/B4/B5/B7/B12/B13/B17/B25/B26/B66/B71 LTE-TDD: B38/B41/B42/B43/B48	-EA	5G NR: FDD: N1/N3/N5/N7/N8/N20/N28 TDD: N38/N40/N41/N77/N78 LTE-FDD: B1/B3/B5/B7/B8/B20/B28 LTE-TDD: B38/B40/B41/B42/B43
	-EA	5G NR: FDD: N1/N3/N5/N7/N8/N20/N28 TDD: N38/N40/N41/N77/N78 LTE-FDD: B1/B3/B5/B7/B8/B20/B28 LTE-TDD: B38/B40/B41/B42/B43	-NA	5G NR: FDD: N2/N5/N7/N8/N28/N66/N71 TDD: N38/N40/N78 LTE-FDD: B1/B2/B3/B4/B5/B7/B8/B25/B26/B28/B66/B71 LTE-TDD: B38/B40/B41/B42/B43
Modulation type	DL: QPSK, 16QAM, 64QAM and 256QAM UL: BPSK, QPSK, 16QAM, 64QAM and 256QAM		DL: QPSK, 16QAM, 64QAM and 256QAM UL: BPSK, QPSK, 16QAM, 64QAM	
Sub-Carrier Spacing(SCS)	SCS support 15KHz and 30KHz		SCS support 15KHz and 30KHz	
5G DL 4×4 MIMO Band	—		—	
5G UL 2×2 MIMO Band	—		—	
Weight	<8g		<8g	
Working Temperature	Normal operating temperature: -30°C ~ +75°C Extended operating temperature: -40°C ~ +85°C		Normal operating temperature: -30°C ~ +75°C Extended operating temperature: -40°C ~ +85°C	
Data Transmission				
5G NR Speed	Sub6G: -Downlink up to 220Mbps -Uplink up to 100Mbps		Sub6G: -Downlink up to 220Mbps -Uplink up to 120Mbps	
LTE Speed(Mbps)	-Downlink up to 220Mbps -Uplink up to 100Mbps		-Downlink up to 150Mbps -Uplink up to 50Mbps	
WCDMA Speed(Kbps)	—		—	
Interface				
SIM	1.8V/3V x2		1.8V/3V x2	
eSIM	•		•	
UART	•		•	
USB	USB 2.0		USB 2.0	
PCIe	PCIe 2.0		PCIe 2.0	
RGMII	SGMII		RGMII	
I2C	•		•	
PCM Voice	•		•	
ADC	•		•	
GPIO	•		•	
Antenna	ANT_PRI/ANT_DIV x2 GNSS: x1		ANT_PRI/ANT_DIV x2 GNSS: x1	
Special Function				
TTS	•		*	
TCP/IP	•		•	
FTP	*		*	
HTTP	*		*	
RIL Driver	Android 4.2/4.4/5.0/5.1/6.0/7.0/8.0/9.0/10.0		Android 4.2/4.4/5.0/5.1/6.0/7.0/8.0/9.0/10.0	
NDIS/NCM	Windows 7/8/10/11		Windows 7/8/10/11	
ECM	•		•	
Gobinet	Linux 2.6 or later		—	
GNSS	•		—	
USB Audio Class (UAC)	•		*	
IP Passthrough	•		*	
Firmware Update	USB/DFOTA		USB/DFOTA	
Electrical Parameter				
Supply Voltage	3.3V~4.35V, typ.3.8V		3.3V~4.35V, typical 3.8V	
Sleep Power Consumption	<6mA		<6mA	
Certifications				
Certifications	CCC*/SRRC*/CTA*/CE*/FCC*		CCC*/SRRC*/CTA*/CE*/FCC*	
Recommended Applications				
Application Fields	It can be widely used in CPE home gateway, TV, AR/VR, industrial router, set-top Box, carrier terminal, video surveillance, industrial interconnection and other fields.			

MeiG AI Computing Module Series





Product	SNM980	SNM970	SNM960	SNM950	SNM930/930L
Product Picture					
OS	Android	Android/Linux	Android	Android/Linux	Android/Linux
CPU	Octa-core	Octa-core	Octa-core	Octa-core	Octa-core
GPU	Adreno™ 830	Adreno™ GPU 740	Adreno™ GPU 730	Adreno™ GPU 650	Adreno™ GPU 642/635
DPU	dual HVX + 4K-HMX	4x HVX NPU:1xHTA	4x HVX NPU:230	4x HVX NPU:230	dual HVX + 2K-HMX
AI(cDSP)	~64 Tops(int 8)	48 Tops	27 Tops	15 Tops	3~8 Tops
Memory	256+16/512+24(GB)	128+8/128+16/256+16(GB)	128+8/128+12/256+12(GB)	128+8/128+12/256+12(GB)	64+4/128+6/128+8(GB)
Package	LGA	LGA:491Pin	LGA:491Pin	LGA:491Pin	LGA:458Pin
Dimension(mm)	42.0*47.0*2.7	45.0x40.0x2.7	45.0x40.0x2.7	45.0x40.0x2.7	47.0x48.0x3.0
Supply Voltage	3.5V~4.35V, typ.3.8V	3.5V~4.35V, typ.3.8V	3.5V~4.35V, typ.3.8V	3.5V~4.35V, typ.3.8V	3.5V~4.35V, typ.3.8V
Working Temperature	-25°C~+75°C	-30°C~+75°C	-30°C~+75°C	-30°C~+75°C	-30°C~+75°C
Storage Temperature	-40°C~+90°C	-40°C~+85°C	-40°C~+85°C	-40°C~+85°C	-40°C~+85°C
Special Function					
Firmware Upgrade	Upgrade through USB interface	Upgrade through USB interface	Upgrade through USB interface	Upgrade through USB interface	Upgrade through USB interface
WLAN	Wi-Fi 7: 802.11be, 2 × 2 MIMO	Wi-Fi7 (2x2 MU-MIMO 802.11a/b/g/n/ac/ax/BE)	Wi-Fi 6E(2 × 2 MU-MIMO 802.11a/b/g/n/ac/ax)	Wi-Fi 6E(2 × 2 MU-MIMO 802.11a/b/g/n/ac/ax)	Wi-Fi 6E(2 × 2 MU-MIMO 802.11a/b/g/n/ac/ax)
BT	BT6.0	BT5.3	BT5.2	BT5.1	BT5.2
Interface					
Display	Two screen/three screen 2*4-lane MIPI-DSI Maximum Resolution: 3840 x 2560@144Hz	Two screen/three screen 2*4-lanes MIPI_DSI 1* DP Maximum Resolution: 3480 x 2160@120 Hz 3360 x 1600@144 Hz	Two screen/three screen 2*4-lanes MIPI_DSI 1* DP 1* 5120 x 2880@60Hz 2* 3840 x 2160@60Hz	Two screen/three screen 2*4-lanes MIPI_DSI 1* DP Maximum Resolution: 2560*1600@60Hz	dual screen 1*4-lanes MIPI_DSI 1* DP FHD+1080*2520@60fps+4K@60fps
Camera	6*4-lane MIPI-CSI (36M+36M+36M or 64M+36M or 108MP)@30fps	8 * 4-lane MIPI-CSI (36+36+36MP) @30fps - triple camera (64+36MP) @30fps - dual camera 108MP @30fps	6 * 4-lane MIPI-CSI (28+28+28MP) @30fps - triple camera (64+25MP) @30fps - dual camera 108MP @30fps	6*4-lane MIPI-CSI (25+25MP or 64MP) @30fps	5*4-lane MIPI-CSI (22+22+22MP or 64MP) @30fps
Video	Encode:4K240/8K60- H.264/ H.265/VP9 Decode:4K120/8K30- H.264/ H.265	Encode: 4K@240fps/8K@60fps H.264/H.265/VP9 Decode: 4K@120fps/8K@30fps H.264/H.265 Concurrency: 4K@60fps decode + 4K@60fps encode	Encode: 4K@240fps/8K@60fps H.264/H.265/VP8/VP9/MPEG-2 Decode: 4K@120fps/8K@30fps H.264/H.265/VP8 Concurrency: 4K@60fps decode + 4K@60fps encode	Encode: 4K@240fps/8K@60fps H.264/H.265/VP8/VP9/MPEG-2 Decode: 4K@120fps/8K@30fps H.264/H.265/VP8 Concurrency: 4K@60fps decode + 4K@30fps encode	Encode: 4K@60fps H.264/H.265/VP9 Decode: 4K@30fps H.264/H.265 Concurrency: 1080P@60fps decode + 1080P@60fps encode
Audio	Mp3;AAC+,eAAC;AMR-NB, -WB,G.711,WMA 9/10 Pro	Mp3;AAC+,eAAC;AMR-NB, -WB,G.711,WMA 9/10 Pro	Mp3;AAC+,eAAC;AMR-NB, -WB,G.711,WMA 9/10 Pro	Mp3;AAC+,eAAC;AMR-NB, -WB,G.711,WMA 9/10 Pro	Mp3;AAC+,eAAC;AMR-NB, -WB,G.711,WMA 9/10 Pro
Hardware Interface	USB 3.1 Gen2*1,Support OTG	USB 3.1 *1, Support OTG	USB 3.1 *1, Support OTG	USB 3.1*1, USB 2.0*1, Support OTG	USB 3.1 *1, USB2.0*1, Support OTG
	UART*3	UART*3	UART*3	UART*7	UART*3
	I2C*3	I2C*3	I2C*7	I2C*12	I2C*5
	SPI*5	SPI*5	SPI*6	SPI*5	SPI*2
	ADC*2	ADC*2	ADC*6	ADC*4	ADC*2
	GPIO*35	GPIO*35	GPIO*40	GPIO*57	GPIO*19
	PCIE *1	PCIE *1	PCIE *1	PCIE *2	PCIE *1
SDIO*1	SDIO*1	SDIO*1	SDIO*1	SDIO*1	
Certifications					
Certifications	CCC*	CCC*	CCC*	CCC*	CCC
Recommended Applications					
Application Fields	It can be widely used in cloud game server, video conference system, VR camera, intelligent robot, video acquisition and processing equipment and other fields.				



MeiG Smart 4G SoC Module Series

Product	SLM927		SLM927M			
Product Picture						
OS	Android		Android			
CPU	Octa-core		Octa-core			
Memory	32+3/64+4/128+8(GB)		32+3/64+4/128+8(GB)			
Band(MHz)	-EAU	LTE-FDD:B1/B3/B5/B7/B8/B20/B28 LTE-TDD:B38/B40/B41(2496-2690MHz)	WCDMA:B1/B2/B5/B8 GSM:850/900/1800/1900	-EAU	LTE-FDD:B1/B3/B5/B7/B8/B20/B28 LTE-TDD:B38/B40/B41(2496-2690MHz)	WCDMA:B1/B2/B5/B8 GSM:850/900/1800/1900
	-CN	LTE-FDD:B1/B3/B5/B8 LTE-TDD:B34/B38/B39/B40/B41(2535-2655MHz)	WCDMA:B1/B8 GSM:900/1800	-CN	LTE-FDD:B1/B3/B5/B8 LTE-TDD:B34/B38/B39/B40/B41(2535-2655MHz)	WCDMA:B1/B8 GSM:900/1800
	-JP	LTE-FDD:B1/B3/B8/B18/B19/B26 LTE-TDD:B41	WCDMA:B1/B3/B6/B8/B19 GSM:900/1800	-JP	LTE-FDD:B1/B3/B8/B18/B19/B26 LTE-TDD:B41	WCDMA:B1/B3/B6/B8/B19 GSM:900/1800
	-A	LTE-FDD:B2/B4/B5/B7/B12/B13/B14/B17/B25/B26/B66/B71 LTE-TDD:B41(2496-2690MHz)	WCDMA:B2/B4/B5	-A	LTE-FDD:B2/B4/B5/B7/B12/B13/B14/B17/B25/B26/B66/B71 LTE-TDD:B41(2496-2690MHz)	WCDMA:B2/B4/B5
Package	LCC:148Pin+LGA:128Pin		LCC:148Pin+LGA:128Pin			
Dimension(mm)	41.0x41.0x2.6		41.0x41.0x2.6			
4G	LTE Cat.6		LTE Cat.6			
Supply Voltage	3.5V~4.35V, typ.3.8V		3.5V~4.35V, typ.3.8V			
Working Temperature	-30°C~+75°C		-30°C~+75°C			
Storage Temperature	-40°C~+85°C		-40°C~+85°C			
Data Transmission						
LTE Speed(Mbps)	Max 300(DL)/50(UL)		Max 300(DL)/50(UL)			
DC-HSPA+Speed(Mbps)	Max 42(DL)/Max 11(UL)		Max 42(DL)/Max 11(UL)			
WCDMA Speed(Kbps)	Max 384(DL)/Max 384(UL)		Max 384(DL)/Max 384(UL)			
TD-SCDMA Speed(Mbps)	Max 4.2(DL)/Max2.2(UL)		Max 4.2(DL)/Max2.2(UL)			
EDGE Speed(Kbps)	Max 236.8(DL)/Max 236.8(UL)		Max 236.8(DL)/Max 236.8(UL)			
GPRS Speed(Kbps)	Max 86.5(DL)/Max 86.5(UL)		Max 86.5(DL)/Max 86.5(UL)			
SMS	•		•			
CSD	•		•			
Special Function						
Firmware Upgrade	Upgrade through USB interface		Upgrade through USB interface			
VoLTE	•		•			
WLAN	2.4G&5G,802.11 a/b/g/n/ac/ax ready		2.4G&5G,802.11 a/b/g/n/ac/ax ready			
BT	BT5.1		BT5.1			
FM	—		—			
GNSS	GPS/Beidou/Glonass		GPS/Beidou/Glonass			
Interface						
Display	1x 4-lane MIPI_DSI FHD+ (1080x2520) @60Hz/90Hz		1x 4-lane MIPI_DSI FHD+ (1080x2520) @60Hz/90Hz			
Camera	3x 4-lane MIPI_CSI interface Support 3x ISP Triple camera: 13 + 13 + 5 MP@30fps ZSL (13+13+5MP) @30fps triple camera (16+15MP or 25+5MP) @30fps dual camera 32MP or 64MP @30fps single camera		3x 4-lane MIPI_CSI interface Support 2x ISP (13+13MP or 25MP) @30fps dual camera 16MP @30fps single camera			
Video	Encode:1080P@60fps HEVC/H.264/H.265/VP9 Decode: 1080P@60fps HEVC/H.264/H.265 Concurrency: 1080P@30fps decode + 1080P@30fps encode		Encode: 1080P@60fps HEVC/H.264/H.265/VP9 Decode: 1080P@60fps HEVC/H.264/H.265 Concurrency: 1080P@30fps decode + 1080P@30fps encode			
Audio	Simulated audio: speaker, earpiece, headphones, 3 sets of microphones Supports 1 set of noise cancelling microphones		Simulated audio: earpiece, headphones, 3 sets of microphones Supports 1 set of noise cancelling microphones			
Hardware Interface	USB 2.0/3.1*1, Support OTG		USB 2.0/3.1*1, Support OTG			
	UART*2		UART*2			
	I2C*5		I2C*5			
	SPI*1		SPI*1			
	ADC*2		ADC*2			
	USIM*2		USIM*2			
	SDIO*1		SDIO*1			
GPIO*19		GPIO*19				
Antenna	Main antenna , Diversity antenna , GNSS Antenna , Wi-Fi/BT Antenna		Main antenna , Diversity antenna , GNSS Antenna , Wi-Fi/BT Antenna			
Certifications						
Certifications	CCC/CE/FCC/JATE/TELEC		CCC/CE/FCC/JATE/TELEC*			
Recommended Applications						
Application Fields	Smart POS, Security Monitoring, Automotive Device, VR/AR, Information Collection equipment, Smart Robots, Smart Home, Intelligent Hardware, Industrial Smart Handhelds, Smart PAD, UAV, VR Camera, Full-view Camera, Multi-touch Device, Walkie-talkie, Smart Wearables, Vending Machines, Logistics Cabinet etc.					



MeiG Smart 4G SoC Module Series

Product	SLM926	SLM925	
Product Picture			
OS	Android	Android	
CPU	Octa-core	Octa-core	
Memory	16+2/32+3/64+4(GB)	32+3/64+4/128+6(GB)	
Band(MHz)	-C	LTE-FDD:B1/B3/B5/B8 LTE-TDD:B34/B38/B39/B40/B41	LTE-FDD:B1/B3/B5/B8 LTE-TDD:B34/B38/B39/B40/B41
	-E	LTE-FDD:B1/B3/B5/B7/B8/B20/B28 LTE-TDD:B38/B40/B41	LTE-FDD:B1/B3/B5/B7/B8/B20 LTE-TDD:B38/B40/B41
	-A	LTE-FDD:B2/B4/B5/B7/B12/B13/B17/B25/B26/B66 WCDMA:B2/B4/B5/B8	LTE-FDD:B2/B4/B5/B7/B12/B13/B14/B25/B26 LTE-TDD:B41
	-AU	LTE-FDD:B1/B3/B5/B7/B8/B28 LTE-TDD:B40	LTE-FDD:B1/B3/B5/B7/B8/B28 LTE-TDD:B40
	-J	LTE-FDD:B1/B3/B8/B18/B19/B26 LTE-TDD:B41	LTE-FDD:B1/B3/B8/B18/B19/B26 LTE-TDD:B41
	-LA	LTE-FDD:B2/B4/B5/B7/B8/B25/B28/B66 LTE-TDD:B40	LTE-FDD:B2/B4/B5/B7/B8/B28 LTE-TDD:B40
Package	LCC 160pin+LGA 112pin	LCC 152pin+LGA 171pin	
Dimension(mm)	41.0x45.5x2.85	43.0x44.0x2.85	
4G	LTE Cat.4/6	LTE Cat.6	
Supply Voltage	3.5V~4.35V, typ.3.8V	3.5V~4.35V, typ.3.8V	
Working Temperature	-30°C~+75°C	-30°C~+75°C	
Storage Temperature	-40°C~+85°C	-40°C~+85°C	
Data Transmission			
LTE Speed(Mbps)	Cat.4 FDD: Maximum 300Mbps (DL)/50Mbps (UL) Cat.4 TDD: Maximum 265Mbps (DL)/35Mbps (UL)	Max 300(DL)/50(UL)	
DC-HSPA+Speed(Mbps)	5.76Mbps (UL)/42Mbps (DL)	Max 42(DL)/Max 11(UL)	
WCDMA Speed(Kbps)	Max 384(DL)/Max 384(UL)	Max 384(DL)/Max 384(UL)	
TD-SCDMA Speed(Mbps)	Max 4.2(DL)/Max 2.2(UL)	Max 4.2(DL)/Max 2.2(UL)	
EDGE Speed(Kbps)	•	Max 236.8(DL)/Max 236.8(UL)	
GPRS Speed(Kbps)	•	Max 86.5(DL)/Max 86.5(UL)	
SMS	•	•	
CSD	•	•	
Special Function			
Firmwart Upgrade	Upgrade through USB interface	Upgrade through USB interface	
VoLTE	•	•	
WLAN	2.4G&5G,802.11 a/b/g/n/ac	2.4G&5G,802.11 a/b/g/n/ac	
BT	BT5.0	BT4.2	
FM	•	—	
GNSS	GPS/Beidou/Glonass	GPS/Beidou/Glonass/Galileo/QZSS	
Interface			
Display	4-lane MIPI_DSI, FHD+(2520*1080) @60fps	1*4 lanes MIPI_DSI, 1* DisplayPort, FHD+ 1080*2520@60fps	
Camera	3*ISP Host Camera: 4-lane MIPI_CSI; Assist Camera: 4-lane MIPI_CSI ; (13+13+5MP)@30fps triple camera (25+5MP) or 13+13MP@30fps dual camera (16+6MP) @24fps dual camera	3*MIPI CSI(4/4/4 or 4/4/2)1*ISP(16+16MP or 25MP) at 30fps ZSL	
Video	Encode: 1080P@60fps H.264/H.265/VP9 Decode: 1080P@60fps H.264/H.265 Concurrency: 1080P@30fps decode + 1080P@30fps encode	Encode: 4K@30fps 8bit H.264/VP8; 4K@30fps 10-bit HEVC, VP9 1080P@60fps, MPEG-2 Decode: 4K@30fps, 10-bit HEVC and 4K@30fps H.264/VP8 4K@30fps Decode+1080P@30fps Encode Concurrency: 4K@30fps decode + 1080P@30fps encode	
Audio	Simulated audio: speaker, earpiece, headphones, 3 sets of microphones Supports 1 set of noise cancelling microphones	Mp3;AAC;HE ACC v1,v2;WMA 9/Pro;Dolby AC-3,eAc-3,DTS-HD,FLAC,APE,ALAC, AIFF and EVS	
Hardware Interface	USB 2.0/3.1*1, 支持OTG	USB 3.1*1	
	UART*3	UART*3	
	I2C*7	I2C*5	
	SPI*2	SPI*2	
	ADC*2	ADC*2	
	USIM*2	USIM*2	
SDIO*1	SDIO*1		
GPIO*27	GPIO*19		
Antenna	Main antenna , Diversity antenna , GNSS Antenna , Wi-Fi/BT Antenna	Main antenna , Diversity antenna , GNSS Antenna , Wi-Fi/BT Antenna	
Certifications			
Certifications	CCC*	CCC/CE*/FCC*/CTA*/PTCRB*	
Recommended Applications			
Application Fields	Smart POS, Security Monitoring, Automotive Device, VR/AR, Information Collection equipment, Smart Robots, Smart Home, Intelligent Hardware, Industrial Smart Handhelds, Smart PAD, UAV, VR Camera, Full-view Camera, Multi-touch Device, Walkie-talkie, Smart Wearables, Vending Machines, Logistics Cabinet etc.		



MeiG Smart 4G SoC Module Series

Product	SLM920	SLM900				
Product Picture						
OS	Android	Android				
CPU	Octa-core	Octa-core				
Memory	32+3/64+4/128+6(GB)	32+3/64+4(GB)				
Band(MHz)	-C	LTE-FDD:B1/B3/B5/B8 LTE-TDD:B34/B38/B39/B40/B41	WCDMA:B1/B8 GSM:900/1800 EVDO/CDMA:BC0 TD-SCDMA:B34/B39	-A	LTE-FDD:B2/B4/B5/B7/B12/B13/B17/B25/B26/B66 WCDMA:B2/B4/B5	GSM:850/1900
	-E	LTE-FDD:B1/B3/B5/B7/B8/B20 LTE-TDD:B38/B40/B41	WCDMA:B1/B5/B8 GSM:850/900/1800	-C	LTE-FDD:B1/B3/B5/B8 LTE-TDD:B34/B38/B39/B40/B41	GSM:850/900/1800 WCDMA:B1/B8 CDMA 1X/EVDO:BC0
	-A	LTE-FDD:B2/B4/B5/B7/B12/B13/B14/B17/B25/B26/B66 LTE-TDD:B41	WCDMA:B1/B2/B5/B8 GSM:850/900/1800/1900	-E	LTE-FDD:B1/B3/B5/B7/B8/B20 LTE-TDD:B38/B40/B41	WCDMA:B1/B2/B5/B8 GSM:850/900/1800
	-AU	LTE-FDD:B1/B3/B5/B7/B8/B28 LTE-TDD:B40	WCDMA:B1/B2/B5/B8 GSM:850/900/1800/1900	-LA	LTE-FDD:B2/B4/B5/B7/B8/B28 LTE-TDD:B40	WCDMA:B2/B5/B8 GSM:850/900/1900
	-J*	LTE-FDD:B1/B3/B8/B18/B19/B26 LTE-TDD:B41	WCDMA:B1/B6/B8/B19			
	-LA*	LTE-FDD:B2/B4/B5/B7/B8/B28 LTE-TDD:B40	WCDMA:B2/B5/B8 GSM:850/900/1900			
	(Global)	Only supported Wi-Fi & BT				
Package	LCC 160pin+LGA 112pin	LCC 160pin+LGA 112pin				
Dimension(mm)	41.0x45.5x2.85	41.0x45.5x2.85				
4G	LTE Cat.6	LTE Cat.6				
Supply Voltage	3.5V~4.35V, typ.3.8V	3.5V~4.35V, typ.3.8V				
Working Temperature	-30°C~+75°C	-30°C~+75°C				
Storage Temperature	-40°C~+85°C	-40°C~+85°C				
LTE Speed(Mbps)	Max 300(DL)/50(UL)	Max 300(DL)/50(UL)				
DC-HSPA+Speed(Mbps)	Max 42(DL)/Max 11(UL)	Max 42(DL)/Max 11(UL)				
WCDMA Speed(Kbps)	Max 384(DL)/Max 384(UL)	Max 384(DL)/Max 384(UL)				
TD-SCDMA Speed(Mbps)	Max 4.2(DL)/Max 2.2(UL)	Max 4.2(DL)/Max 2.2(UL)				
EDGE Speed(Kbps)	Max 236.8(DL)/Max 236.8(UL)	Max 236.8(DL)/Max 236.8(UL)				
GPRS Speed(Kbps)	Max 86.5(DL)/Max 86.5(UL)	Max 86.5(DL)/Max 86.5(UL)				
SMS	•	•				
CSD	•	•				
Firmware Upgrade	Upgrade through USB interface	Upgrade through USB interface				
VoLTE	•	•				
WLAN	2.4G&5G,802.11 a/b/g/n/ac	2.4G&5G,802.11 a/b/g/n/ac				
BT	BT4.2/BT5.0	BT5.X				
FM	—	•				
GNSS	GPS/Beidou/Glonass	GPS/Beidou/Glonass/Galileo/QZSS				
Display	1*4 lanes MIPI_DSI, 1* DisplayPort, FHD+ 1080*2520@60fps	Support Two LCMs; 4 lanes MIPI DSI 2560*1600 60fps(WQSGA)				
Camera	(16+16MP or 25MP) @30fps dual camera 16MP @fps single camera	MIPI_CSI, support three cameras Double ISP up to 16MP 4-lane MIPI_CSI for rear camera, up to 24MP 4-lane MIPI_CSI for front camera, up to 16MP				
Video	Encode: 4K@30fps 8 bit H.264/VP8; 4K@30fps 10bit HEVC/VP9; 1080P@60fps MPE Decode: 4K@30fps 10 bit HEVC+4K@30fps H.264/VP8 Concurrency: 4K@30fps decode + 1080P@30fps encode	Encode: 4K@30fps 8 bit H.264/VP8; 4K@30fps 10bit HEVC/VP9; 1080P@60fps MPE Decode: 4K@30fps 10 bit HEVC+4K@30fps H.264/VP8 Concurrency: 4K@30fps decode + 1080P@30fps encode				
Audio	Mp3, AAC+, eAAC, AMR-NB, -WB, G.711, WMA 9/10 Pro	Mp3; aacPlus, eAAC; AMR-NB, AMR-WB, G.711, Windows Media Audio(WMA) 9/10 Pro				
Hardware Interface	USB 2.0*1, USB 3.1*1, Support OTG	USB 2.0/3.0*1, Support OTG				
	UART*3	UART*3				
	I2C*5	I2C*5				
	SPI*2	SPI*2				
	ADC*2	ADC *2				
	USIM*2	GPIO*19				
	SDIO*1	SIM卡 *2				
GPIO*19	SDIO *1					
Antenna	Main antenna , Diversity antenna , GNSS Antenna , Wi-Fi/BT Antenna	Main antenna , Diversity antenna , GNSS Antenna , Wi-Fi/BT Antenna				
Certifications	CCC/CE/FCC/JATE/TELEC	CCC/CE/FCC/ROHS/JATE/TELEC/CTA*/PTCRB*				
Application Fields	Smart POS, Security Monitoring, Automotive Device, VR/AR, Information Collection equipment, Smart Robots, Smart Home, Intelligent Hardware, Industrial Smart Handhelds, Smart PAD, UAV, VR Camera, Full-view Camera, Multi-touch Device, Walkie-talkie, Smart Wearables, Vending Machines, Logistics Cabinet etc.					



MeiG Smart 4G SoC Module Series

Product	SLM759	SLM758		
Product Picture				
OS	Android	Android		
CPU	Octa-core	Octa-core		
Memory	16+2/32+3/64+4(GB)	16+2/32+3/64+4(GB)		
Band(MHz)	-A	LTE-FDD:B2/B4/B5/B7/B12/B13/B17/B25/B26 LTE-TDD:B41 WCDMA:B1/B2/B4/B5 GSM:850/1800	-A	LTE-FDD:B2/B4/B5/B12/B13/B17/B28 WCDMA:B2/B4/B5
	-E	LTE-FDD:B1/B3/B5/B7/B8/B20/B28A LTE-TDD:B38/B40/B41 WCDMA:B1/B2/B5/B8 GSM:850/900/1800/1900	-C	LTE-FDD:B1/B3/B5/B8 WCDMA:B1/B5/B8 LTE-TDD:B38/B39/B40/B41 TDS:B34/B39 EVDO&CDMA:BC0 GSM:850/900/1800
	-J	LTE-FDD:B1/B3/B8/B19/B26 LTE-TDD:B41 WCDMA:B1/B6/B8/B19	-E	LTE-FDD:B1/B3/B5/B7/B8/20 LTE-TDD:B38/B40/B41 WCDMA:B1/B5/B8 GSM:850/900/1800
	-AU	LTE-FDD:B1/B3/B5/B7/B8/B28 LTE-TDD:B40 WCDMA:B1/B2/B5/B8 GSM:850/900/1800/1900	-J	LTE-FDD:B1/B3/B8/B9/B19/B26/B28 WCDMA:B1/B8/B9/B19
	-LA	LTE-FDD:B2/B4/B5/B7/B8/B28 LTE-TDD:B40 WCDMA:B2/B5/B8 GSM:850/1800/1900	-AU	LTE-FDD:B1/B3/B5/B7/B8/B28 LTE-TDD:B38/B40/B41 WCDMA:B1/B5/B8 GSM:850/900/1800
	(WiFi-Only)	Wi-Fi:802.11 a/b/g/n/ac* BT4.2		
	Package	LCC 160pin+LGA 112pin	LCC 160pin+LGA 112pin	
Dimension(mm)	43.0x44.0x2.85	41.0x45.5x2.85		
4G	LTE Cat.4	LTE Cat.4		
Supply Voltage	3.5V~4.35V, typ.3.8V	3.5V~4.35V, typ.3.8V		
Working Temperature	-30°C~+75°C	-30°C~+75°C		
Storage Temperature	-40°C~+85°C	-40°C~+85°C		
Data Transmission				
LTE Speed(Mbps)	Max 150(DL)/50(UL)	Max 150(DL)/50(UL)		
DC-HSPA+Speed(Mbps)	Max 42(DL)/Max 11(UL)	Max 42(DL)/Max 11(UL)		
WCDMA Speed(Kbps)	Max 384(DL)/Max 384(UL)	Max 384(DL)/Max 384(UL)		
TD-SCDMA Speed(Mbps)	Max 4.2(DL)/Max 2.2(UL)	Max 4.2(DL)/Max 2.2(UL)		
EDGE Speed(Kbps)	Max 236.8(DL)/Max 236.8(UL)	Max 236.8(DL)/Max 236.8(UL)		
GPRS Speed(Kbps)	Max 86.5(DL)/Max 86.5(UL)	Max 86.5(DL)/Max 86.5(UL)		
SMS	•	•		
CSD	•	•		
Special Function				
Firmware Upgrade	Upgrade through USB interface	Upgrade through USB interface		
VoLTE	•	•		
WLAN	2.4G&5G,802.11 a/b/g/n ; compatible with 11ac	2.4G&5G,802.11 a/b/g/n ; compatible with 11ac		
BT	BT4.2	BT4.2		
FM	—	—		
GNSS	GPS/Beidou/Glonass/Galileo	GPS/Beidou/Glonass/Galileo		
Interface				
Display	Support Two LCMs;4 lanes MIPI DSI FULL HD:1920*1200 60fps;	Support Two LCMs;4 lanes MIPI DSI FULL HD:1920*1200 60fps;		
Camera	MIPI_CSI,support three cameras Double ISP up to 13MP 4-lane MIPI_CSI for rear camera,up to 24MP 4-lane MIPI_CSI for front camera,up to 13MP	MIPI_CSI,support three cameras Double ISP up to 13MP Double ISP up to 13MP 4-lane MIPI_CSI for rear camera,up to 24MP 4-lane MIPI_CSI for front camera,up to 13MP		
Video	Encode: 4K@30fps or 1080P@60fps H.264 MP4/WMV9/VC1/DivX/VP8/VP9 Decode: 4K@30fps or 1080P@60fps H.264/H.265/MP4/VP8 Concurrency: 1080P@60fps decode + 1080P@60fps encode	Encode: 4K@30fps or 1080P@60fps H.264 MP4/WMV9/VC1/DivX/VP8/VP9 Decode: 4K@30fps or 1080P@60fps H.264/H.265/MP4/VP8 Concurrency: 1080P@60fps decode + 1080P@60fps encode		
Audio	Mp3; aacPlus, eAAC; AMR-NB, AMR-WB, G.711, Windows Media Audio(WMA) 9/10 Pro	Mp3; aacPlus, eAAC; AMR-NB, AMR-WB, G.711, Windows Media Audio(WMA) 9/10 Pro		
Hardware Interface	USB 2.0/3.0*1, Support OTG	USB 2.0/3.0*1, Support OTG		
	UART*4	UART*4		
	I2C*8 (8 sets of BLSPs are available)	I2C*8 (8 sets of BLSPs are available)		
	SPI (8 sets of BLSPs are available)	SPI (8 sets of BLSPs are available)		
	ADC *2	ADC *2		
	GPIO *50	GPIO *50		
	SIM Card*2	SIM Card*2		
	SDIO *1	SDIO *1		
Antenna	Main antenna , Diversity antenna , GNSS Antenna , Wi-Fi/BT Antenna	Main antenna , Diversity antenna , GNSS Antenna , Wi-Fi/BT Antenna		
Certifications				
Certifications	CCC/IC*/FCC*/PTCRB*/CE/GCF/VZ*/CTA/AT&T*	CCC/SRRC/CTA/SRRC/ROHS/CE/FCC/IC/GCF/RCM/PTCRB/JATE & Telec		
Recommended Applications				
Application Fields	Smart POS, Security Monitoring, Automotive Device, VR/AR, Information Collection equipment, Smart Robots, Smart Home, Intelligent Hardware, Industrial Smart Handhelds, Smart PAD, UAV, VR Camera, Full-view Camera, Multi-touch Device, Walkie-talkie, Smart Wearables, Vending Machines, Logistics Cabinet etc.			



MeiG Smart 4G SoC Module Series

Product	SLM757	SLM756				
Product Picture						
OS	Android	Android				
CPU	Quad-core	Quad-core				
Memory	8+1/16+2(GB)	8+1/16+2(GB)				
Band(MHz)	-QA	LTE-FDD:B2/B4/B5/B12B13/B17/B28 WCDMA:B2/B4/B5	-NA	LTE-FDD:B2/B4/B5/B7/B12/B13/B17 WCDMA:B2/B4/B5		
	-QC	LTE-FDD:B1/B3/B5/B8 LTE-TDD:B38/B39/B40/B41 TDS:B34/B39	WCDMA:B1/B5/B8 EVDO&CDMA:BC0 GSM:850/900/1800/1900	-CH	LTE-FDD:B1/B3/B5/B8 LTE-TDD:B38/B39/B40/B41 WCDMA:B1/B5/B8	TD-SCDMA:B34/B39 CDMA1X/EVDO:BC0 GSM:850/900/1800
	-QE	LTE-FDD:B1/B3/B5/B7/B8/B20 LTE-TDD:B38/B40/B41	WCDMA:B1/B5/B8 GSM:850/900/1800	-EU	LTE-FDD:B1/B3/B5/B7/B8/B20 LTE-TDD:B38/B40/B41	WCDMA:B1/B5/B8 GSM:850/900/1800
				-LA	LTE-FDD:B1/B3/B5/B7/B8/B28 LTE-TDD:B40	WCDMA:B1/B2/B5/B8 GSM:850/900/1800/1900
Package	LCC 146pin+LGA 92pin	LCC 130pin+LGA 12pin (GND)				
Dimension(mm)	41.0x41.0x2.85	39.0x44.0x2.85				
4G	LTE Cat.4	LTE Cat.4				
Supply Voltage	3.5V~4.35V, typ.3.8V	3.5V~4.35V, typ.3.8V				
Working Temperature	-30°C~+75°C	-30°C~+75°C				
Storage Temperature	-40°C~+85°C	-40°C~+85°C				
Data Transmission						
LTE Speed(Mbps)	Max 150(DL)/50(UL)	Max 150(DL)/50(UL)				
DC-HSPA+Speed(Mbps)	Max 42(DL)/Max 11(UL)	Max 42(DL)/Max 11(UL)				
WCDMA Speed(Kbps)	Max 384(DL)/Max 384(UL)	Max 384(DL)/Max 384(UL)				
TD-SCDMA Speed(Mbps)	Max 4.2(DL)/Max 2.2(UL)	Max 4.2(DL)/Max 2.2(UL)				
EDGE Speed(Kbps)	Max 236.8(DL)/Max 236.8(UL)	Max 236.8(DL)/Max 236.8(UL)				
GPRS Speed(Kbps)	Max 86.5(DL)/Max 86.5(UL)	Max 86.5(DL)/Max 86.5(UL)				
SMS	•	•				
CSD	•	•				
Special Function						
Firmwart Upgrade	Upgrade through USB interface	Upgrade through USB interface				
VoLTE	•	•				
WLAN	2.4G,802.11 b/g/n 11a/n 5G Wi-Fi*	2.4G&5G*Wi-Fi, 802.11a*/b/g/n				
BT	BT4.2	BT4.1				
FM	•	•				
GNSS	GPS/Beidou/Glonass	GPS/Beidou/Glonass				
Interface						
Display	4 lanes MIPI DSI,HD:1280*800 60fps;	4 lanes MIPI DSI,HD(720P):1280*720@60fps				
Camera	MIPI_CSI,support two cameras 4-lane MIPI_CSI for rear camera,up to 16MP 4-lane MIPI_CSI for front camera,up to 8MP	MIPI_CSI,support two cameras MIPI_CSI,support two cameras 2-lane MIPI_CSI for rear camera,up to 8MP 1-lane MIPI_CSI for front camera,up to 2MP				
Video	Encode: 4K@30fps or 1080P@60fps H.264 MP4/WMV9/VC1/DivX/VP8/VP9 Decode: 4K@30fps or 1080P@60fps H.264/H.265/MP4/VP8 Concurrency: 1080P@60fps decode + 1080P@60fps encode	Encode: 4K@30fps or 1080P@60fps H.264 MP4/WMV9/VC1/DivX/VP8/VP9 Decode: 4K@30fps or 1080P@60fps H.264/H.265/MP4/VP8 Concurrency: 1080P@60fps decode + 1080P@60fps encode				
Audio	Mp3, AAC, He-AAC v1, v2; WMA 9/Pro;Dolby AC-3, eAC-3,DTS-HD M6,DTS-HD M8.	MP3,AAC,AAC+,eAAC,AMR-NB,-WB,G.711,WMA 9/10 Pro				
Hardware Interface	USB *1,Support OTG	USB *1,Support OTG				
	UART*3	UART*2				
	I2C*6 (6 sets of BLSPs are available)	I2C *4				
	SPI (6 sets of BLSPs are available)	SPI *1				
	ADC *2	ADC *2				
	GPIO *53	GPIO*17				
	SIM Card*2	SIM Card*2				
SDIO *1	SDIO *1					
Antenna	Main antenna , Diversity antenna , GNSS Antenna , Wi-Fi/BT Antenna	Main antenna , Diversity antenna , GNSS Antenna , Wi-Fi/BT Antenna				
Certifications						
Certifications	CCC/IC/FCC/PTCRB/CE/CTA/AT&T	CCC/CE/FCC/IC/MIC/Telec & JATE/Softbank				
Recommended Applications						
Application Fields	Smart POS, Security Monitoring, Automotive Device, VR/AR, Information Collection equipment, Smart Robots, Smart Home, Intelligent Hardware, Industrial Smart Handhelds, Smart PAD, UAV, VR Camera, Full-view Camera, Multi-touch Device, Walkie-talkie, Smart Wearables, Vending Machines, Logistics Cabinet etc.					



MeiG Smart 4G SoC Module Series

Product	SLM550	SLM550S		
Product Picture				
OS	Android	Android		
CPU	Quad-core	Quad-core		
Memory	8+1/16+2/32+2/64+4(GB)	8+1/16+2/32+3/64+4(GB)		
Band(MHz)	-C	LTE-FDD:B1/B3/B5/B8 LTE-TDD:B34/B38/B39/B40/B41 WCDMA:B1/B8 EVDO/CDMA:BC0 TD-SCDMA:B34/B39 GSM:900/1800	-C	LTE-FDD:B1/B3/B5/B8 LTE-TDD:B34/B38/B39/B40/B41 WCDMA:B1/B8 EVDO/CDMA:No Support TD-SCDMA:No Support GSM:900/1800
	-E	LTE-FDD:B1/B3/B5/B7/B8/B20/B28A LTE-TDD:B38/B40/B41 WCDMA:B1/B5/B8 GSM:850/900/1800/1900	-E	LTE-FDD:B1/B2/B3/B5/B7/B8/B20/B28 LTE-TDD:B38/B40/B41 WCDMA:B1/B2/B5/B8 GSM:850/900/1800/1900
	-A	LTE-FDD:B2/B4/B5/B7/B12/B13/B17/B25/B26/B66 WCDMA:B2/B4/B5/B8 GSM:850/1900	-AU	LTE-FDD:B1/B3/B5/B7/B8/B28 LTE-TDD:B40 WCDMA:B1/B5/B8 GSM:850/900/1800
	-AU*	LTE-FDD:B1/B3/B5/B7/B8/B28 LTE-TDD:B40 WCDMA:B1/B5/B8 GSM:850/900/1800	-LA	LTE-FDD:B2/B4/B5/B7/B8/B25/B28/B66 LTE-TDD:B40 WCDMA:B2/B5/B8 GSM:850/900/1900
	-J*	LTE-FDD:B1/B3/B8/B18/B19/B26 LTE-TDD:B41 WCDMA:B1/B6/B8/B19		
Package	LCC 146pin+LGA 64pin	LCC 146pin+LGA 128pin		
Dimension(mm)	40.5x40.5x2.85	40.5x40.5x2.85		
4G	LTE Cat.4	LTE Cat.4		
Supply Voltage	3.5V~4.35V, typ.3.8V	3.5V~4.35V, typ.3.8V		
Working Temperature	-30°C~+75°C	-30°C~+75°C		
Storage Temperature	-40°C~+85°C	-40°C~+85°C		
Data Transmission				
LTE Speed(Mbps)	Max 150(DL)/50(UL)	Max 150(DL)/50(UL)		
DC-HSPA+Speed(Mbps)	Max 42(DL)/Max 11(UL)	Max 42(DL)/Max 11(UL)		
WCDMA Speed(Kbps)	Max 384(DL)/Max 384(UL)	Max 384(DL)/Max 384(UL)		
TD-SCDMA Speed(Mbps)	Max 4.2(DL)/Max 2.2(UL)	Max 4.2(DL)/Max 2.2(UL)		
EDGE Speed(Kbps)	Max 236.8(DL)/Max 236.8(UL)	Max 236.8(DL)/Max 236.8(UL)		
GPRS Speed(Kbps)	Max 86.5(DL)/Max 86.5(UL)	Max 86.5(DL)/Max 86.5(UL)		
SMS	•	•		
CSD	•	•		
Special Function				
Firmware Upgrade	Upgrade through USB interface	Upgrade through USB interface		
VoLTE	•	•		
WLAN	2.4G&5G,802.11 a/b/g/n/ac	2.4G&5G,802.11 a*/b*/g*/n/ac*		
BT	BT5.0	BT5.1		
FM	•	•		
GNSS	GPS/Beidou/Glonass	GPS/Beidou/Glonass		
Interface				
Display	4-lane MIPI DSI HD+(720*1680) @60fps	4-lane MIPI_DSI FHD+(1080*2160) @60fps		
Camera	2*MIPI CSI(4/4 or 4/2/1) 2*ISP(13+13MP or 25MP) at 30fps ZSL	Host Camera: 2-lane MIPI_CSI; Assist Camera: 1-lane MIPI_CSI ; Maximum Speed 2.1Gbps/Lane; Can support up to 8M pixel photography		
Video	Encode: 4K@30fps or 1080P@60fps H.264 MP4/WMV9/VC1/DivX/VP8/VP9 Decode: 4K@30fps or 1080P@60fps H.264/H.265/MP4/VP8 Concurrency: 1080P@60fps decode + 1080P@60fps encode	Encode: 4K@30fps or 1080P@60fps H.264 MP4/WMV9/VC1/DivX/VP8/VP9 Decode: 4K@30fps or 1080P@60fps H.264/H.265/MP4/VP8 Concurrency: 1080P@60fps decode + 1080P@60fps encode		
Audio	Mp3; AAC+, eAAC; AMR-NB, -WB, G.711, WMA 9/10 Pro	Simulated audio: speaker, earpiece, headphones, 3 sets of microphones support 1 set of noise cancelling microphones		
Hardware Interface	USB 2.0/3.1*1, Support OTG	USB*1, Support OTG		
	UART*3	UART*3		
	I2C*5	I2C*5		
	SPI*1	SPI*1		
	ADC*1	ADC*2		
	USIM*2	USIM*2		
	SDIO*1	SDIO*1		
	GPIO*40	GPIO*24		
Antenna	Main antenna , Diversity antenna , GNSS Antenna , Wi-Fi/BT Antenna	Main antenna , Diversity antenna , GNSS Antenna , Wi-Fi/BT Antenna		
Certifications				
Certifications	CCC/CE/FCC/IC/Rohs/Anatel*/PTCRB*/AT&T*/Verizon*	CCC*		
Recommended Applications				
Application Fields	Smart POS, Security Monitoring, Automotive Device, VR/AR, Information Collection equipment, Smart Robots, Smart Home, Intelligent Hardware, Industrial Smart Handhelds, Smart PAD, UAV, VR Camera, Full-view Camera, Multi-touch Device, Walkie-talkie, Smart Wearables, Vending Machines, Logistics Cabinet etc.			

MeiG Smart 4G SoC Module Series

Product	SLM755L	SLM500Q																								
Product Picture																										
OS	Android	Android																								
CPU	Quad-core	Quad-core																								
Memory	8+1/16+2(GB)	8+1/16+2/32+3(GB)																								
Band(MHz)	<table border="1"> <tr> <td>-C</td> <td>LTE-FDD:B1/B3/B5/B8 LTE-TDD:B38/B39/B40/B41 TDS:B34/B39</td> <td>WCDMA:B1/B5/B8 EVDO&CDMA:BC0 GSM:850/900/1800</td> </tr> <tr> <td>-E</td> <td>LTE-FDD:B1/B3/B5/B7/B8/B20 LTE-TDD:B38/B40/B41</td> <td>WCDMA:B1/B5/B8 GSM:850/900/1800/1900</td> </tr> </table>	-C	LTE-FDD:B1/B3/B5/B8 LTE-TDD:B38/B39/B40/B41 TDS:B34/B39	WCDMA:B1/B5/B8 EVDO&CDMA:BC0 GSM:850/900/1800	-E	LTE-FDD:B1/B3/B5/B7/B8/B20 LTE-TDD:B38/B40/B41	WCDMA:B1/B5/B8 GSM:850/900/1800/1900	<table border="1"> <tr> <td>-C</td> <td>LTE-FDD:B1/B3/B5/B8 LTE-TDD:B34/B38/B39/B40/B41</td> <td>TD-SCDMA:B34/B39 EVDO/CDMA:BC0 GSM:900/1800</td> </tr> <tr> <td>-E</td> <td>LTE-FDD:B1/B3/B5/B7/B8/B20/B28A LTE-TDD:B38/B40/B41</td> <td>TD-SCDMA:B34/B39 GSM:850/900/1800</td> </tr> <tr> <td>-A</td> <td>LTE-FDD:B2/B4/B5/B7/B12/B13/B14/B25/B26/B66 LTE-FDD:B40</td> <td>WCDMA:B2/B4/B5/B8 GSM:850/1900</td> </tr> <tr> <td>-J</td> <td>LTE-FDD:B1/B3/B8/B18/B19/B26 LTE-TDD:B41</td> <td>WCDMA:B1/B6/B8/B19</td> </tr> <tr> <td>-AU</td> <td>LTE-FDD:B1/B3/B5/B7/B8/B28 LTE-TDD:B40</td> <td>WCDMA:B1/B5/B8 GSM:850/900/1800</td> </tr> <tr> <td>-LA</td> <td>LTE-FDD:B2/B4/B5/B7/B8/B25/B28/B66 LTE-TDD:B40</td> <td>WCDMA:B2/B5/B8 GSM:850/900/1900</td> </tr> </table>	-C	LTE-FDD:B1/B3/B5/B8 LTE-TDD:B34/B38/B39/B40/B41	TD-SCDMA:B34/B39 EVDO/CDMA:BC0 GSM:900/1800	-E	LTE-FDD:B1/B3/B5/B7/B8/B20/B28A LTE-TDD:B38/B40/B41	TD-SCDMA:B34/B39 GSM:850/900/1800	-A	LTE-FDD:B2/B4/B5/B7/B12/B13/B14/B25/B26/B66 LTE-FDD:B40	WCDMA:B2/B4/B5/B8 GSM:850/1900	-J	LTE-FDD:B1/B3/B8/B18/B19/B26 LTE-TDD:B41	WCDMA:B1/B6/B8/B19	-AU	LTE-FDD:B1/B3/B5/B7/B8/B28 LTE-TDD:B40	WCDMA:B1/B5/B8 GSM:850/900/1800	-LA	LTE-FDD:B2/B4/B5/B7/B8/B25/B28/B66 LTE-TDD:B40	WCDMA:B2/B5/B8 GSM:850/900/1900
-C	LTE-FDD:B1/B3/B5/B8 LTE-TDD:B38/B39/B40/B41 TDS:B34/B39	WCDMA:B1/B5/B8 EVDO&CDMA:BC0 GSM:850/900/1800																								
-E	LTE-FDD:B1/B3/B5/B7/B8/B20 LTE-TDD:B38/B40/B41	WCDMA:B1/B5/B8 GSM:850/900/1800/1900																								
-C	LTE-FDD:B1/B3/B5/B8 LTE-TDD:B34/B38/B39/B40/B41	TD-SCDMA:B34/B39 EVDO/CDMA:BC0 GSM:900/1800																								
-E	LTE-FDD:B1/B3/B5/B7/B8/B20/B28A LTE-TDD:B38/B40/B41	TD-SCDMA:B34/B39 GSM:850/900/1800																								
-A	LTE-FDD:B2/B4/B5/B7/B12/B13/B14/B25/B26/B66 LTE-FDD:B40	WCDMA:B2/B4/B5/B8 GSM:850/1900																								
-J	LTE-FDD:B1/B3/B8/B18/B19/B26 LTE-TDD:B41	WCDMA:B1/B6/B8/B19																								
-AU	LTE-FDD:B1/B3/B5/B7/B8/B28 LTE-TDD:B40	WCDMA:B1/B5/B8 GSM:850/900/1800																								
-LA	LTE-FDD:B2/B4/B5/B7/B8/B25/B28/B66 LTE-TDD:B40	WCDMA:B2/B5/B8 GSM:850/900/1900																								
Package	LCC 146pin+LGA 64pin	LCC 146pin+LGA 128pin																								
Dimension(mm)	40.5x40.5x2.85	40.5x40.5x2.85																								
4G	LTE Cat.4	LTE Cat.4																								
Supply Voltage	3.5V~4.35V, typ.3.8V	3.5V~4.35V, typ.3.8V																								
Working Temperature	-30°C~+75°C	-30°C~+75°C																								
Storage Temperature	-40°C~+85°C	-40°C~+85°C																								
Data Transmission																										
LTE Speed(Mbps)	Max 150(DL)/50(UL)	Max 150(DL)/50(UL)																								
DC-HSPA+Speed(Mbps)	Max 42(DL)/Max 11(UL)	Max 42(DL)/Max 11(UL)																								
WCDMA Speed(Kbps)	Max 384(DL)/Max 384(UL)	Max 384(DL)/Max 384(UL)																								
TD-SCDMA Speed(Mbps)	Max 4.2(DL)/Max 2.2(UL)	Max 4.2(DL)/Max 2.2(UL)																								
EDGE Speed(Kbps)	Max 236.8(DL)/Max 236.8(UL)	Max 236.8(DL)/Max 236.8(UL)																								
GPRS Speed(Kbps)	Max 86.5(DL)/Max 86.5(UL)	Max 86.5(DL)/Max 86.5(UL)																								
SMS	•	•																								
CSD	•	•																								
Special Function																										
Firmware Upgrade	Upgrade through USB interface	Upgrade through USB interface																								
VoLTE	•	•																								
WLAN	2.4G&5G*Wi-Fi,802.11a*/b/g/n	2.4G&5G,802.11 a/b/g/n/ac																								
BT	BT4.1	BT4.2																								
FM	•	—																								
GNSS	GPS/Beidou/Glonass	GPS/Beidou/Glonass/Galileo																								
Interface																										
Display	4 lanes MIPI DSI,HD(720P):1280*720@60fps	1*MIPI DSI;1440*720@60Hz																								
Camera	MIPI_CSI,support two cameras 2-lane MIPI_CSI for rear camera,up to 8MP 1-lane MIPI_CSI for front camera,up to 2MP	MIPI_CSI,support two cameras 4-lane MIPI_CSI for rear camera,up to 13MP 2-lane MIPI_CSI for front camera,up to 5MP																								
Video	Encode: 4K@30fps or 1080P@60fps H.264 MP4/WMV9/VC1/DivX/VP8/VP9 Decode: 4K@30fps or 1080P@60fps H.264/H.265/MP4/VP8 Concurrency: 1080P@60fps decode + 1080P@60fps encode	Encode: 4K@30fps or 1080P@60fps H.264 MP4/WMV9/VC1/DivX/VP8/VP9 Decode: 4K@30fps or 1080P@60fps H.264/H.265/MP4/VP8 Concurrency: 1080P@60fps decode + 1080P@60fps encode																								
Audio	MP3,AAC,AAC+,eAAC,AMR-NB,-WB,G.711,WMA 9/10 Pro	Mp3;AAC+,eAAC;AMR-NB,-WB,G.711,WMA 9/10 Pro																								
Hardware Interface	USB *1, Support OTG	USB *1, Support OTG																								
	UART*2	UART*3																								
	I2C *4	I2C*5																								
	SPI *1	SPI*5																								
	ADC *2	ADC*2																								
	GPIO *24	GPIO*24																								
	SIM卡 *2	SIM卡 *2																								
SDIO *1	SDIO *1																									
Antenna	Main antenna , Diversity antenna , GNSS Antenna , Wi-Fi/BT Antenna	Main antenna , Diversity antenna , GNSS Antenna , Wi-Fi/BT Antenna																								
Certifications																										
Certifications	CCC/CE/ROHS/FCC/CTA*/PTCRB*	CCC/CE/FCC/IC/ROHS/JATE&Telec/MIC/Docomo/PTCRB/GCF/AT&T/RCM/Verizon/Anatel																								
Recommended Applications																										
Application Fields	Smart POS, Security Monitoring, Automotive Device, VR/AR, Information Collection equipment, Smart Robots, Smart Home, Intelligent Hardware, Industrial Smart Handhelds, Smart PAD, UAV, VR Camera, Full-view Camera, Multi-touch Device, Walkie-talkie, Smart Wearables, Vending Machines, Logistics Cabinet etc.																									

MeiG Smart 4G SoC Module Series

Product	SLM500L	SLM500S		
Product Picture				
OS	Android	Android		
CPU	Octa-core	Quad-core		
Memory	16+2/32+3/64+4(GB)	8+1/16+2/32+3(GB)		
Band(MHz)	-C	LTE-FDD:B1/B3/B5/B8 LTE-TDD:B34/B38/B39/B40/B41 WCDMA:B1/B8	EVDO/CDMA:BC0 TD-SCDMA:B34/B39 GSM:900/1800	
	-E	LTE-FDD:B1/B3/B5/B7/B8/B28A LTE-TDD:B38/B40/B41 WCDMA:B1/B5/B8	GSM:850/900/1800/1900	
	-A	LTE-FDD:B2/B4/B5/B7/B12/B13/B17/B25/B26/B66 WCDMA:B2/B4/B5/B8	GSM:850/1900	
	-J	LTE-FDD:B1/B3/B8/B18/B19/B26 LTE-TDD:B41 WCDMA:B1/B6/B8/B19		
		-C	LTE-FDD:B1/B3/B5/B8 LTE-TDD:B34/B38/B39/B40/B41 WCDMA:B1/B8	GSM:900/1800
		-E	LTE-FDD:B1/B3/B5/B7/B8/B20 LTE-TDD:B38/B40/B41 WCDMA:B1/B5/B8	GSM:850/900/1800/1900
		-AU/LA	LTE-FDD:B2/B4/B5/B7/B8/B28 LTE-TDD:B34/B38/B39/B40/B41 WCDMA:B2/B4/B5/B8	GSM:850/900/1800/1900
Package	LCC 146pin+LGA 128pin	LCC 146pin+LGA 128pin		
Dimension(mm)	40.5x40.5x2.85	40.5x40.5x2.85		
4G	LTE Cat.4	LTE Cat.4		
Supply Voltage	3.5V~4.35V, typ.3.8V	3.5V~4.35V, typ.3.8V		
Working Temperature	-30°C~+75°C	-30°C~+75°C		
Storage Temperature	-40°C~+85°C	-40°C~+85°C		
Data Transmission				
LTE Speed(Mbps)	Max 150(DL)/50(UL)	Max 150(DL)/50(UL)		
DC-HSPA+Speed(Mbps)	Max 42(DL)/Max 11(UL)	Max 42(DL)/Max 11(UL)		
WCDMA Speed(Kbps)	Max 384(DL)/Max 384(UL)	Max 384(DL)/Max 384(UL)		
TD-SCDMA Speed(Mbps)	Max 4.2(DL)/Max 2.2(UL)	Max 4.2(DL)/Max 2.2(UL)		
EDGE Speed(Kbps)	Max 236.8(DL)/Max 236.8(UL)	Max 236.8(DL)/Max 236.8(UL)		
GPRS Speed(Kbps)	Max 86.5(DL)/Max 86.5(UL)	Max 86.5(DL)/Max 86.5(UL)		
SMS	•	•		
CSD	•	•		
Special Function				
Firmwarr Upgrade	Upgrade through USB interface	Upgrade through USB interface		
VoLTE	•	•		
WLAN	2.4G&5G,802.11 a/b/g/n/ac*	2.4G,802.11 b/g/n		
BT	BT4.2	BT4.2		
FM	—	—		
GNSS	GPS/Beidou/Glonass/Galileo	GPS/Beidou/Glonass		
Interface				
Display	1*MIPI DSI;1920*1200@60Hz	1*4 lanes MIPI DSI ,HD(720P):1440*720@60fps		
Camera	MIPI_CSI,support two cameras 4-lane MIPI_CSI for rear camera,up to 21MP(24MP) 4-lane MIPI_CSI for front camera,up to 13MP	MIPI_CSI,support two cameras 4-lane MIPI_CSI for rear camera,up to 13MP 2-lane MIPI_CSI for front camera,up to 5MP		
Video	Encode: 4K@30fps 1080P@60fps H.264/H.265 MP4/WMV9/VC1/DivX/VP8/VP9 Decode: 4K@30fps 1080P@60fps H.264/H.265 MP4/VP8 Concurrency: 1080P@60fps decode + 1080P@30fps encode	Encode: 1080P@30fps HEVC/H.264/MP4/DivX/VP8 WVGA 30fps H.263 Decode: 720P@30fps H.264/MP4/DivX/VP8 WVGA 30fps H.263 Concurrency: 1080P@30fps decode + 1080P@30fps encode		
Audio	MP3,aacPlus,eAAC,ARM-NB,AMR-WB,G.711,Windows Media Audio(WMA)9/10 Pro	Mp3;AAC+,eAAC;AMR-NB,-WB,G.711,WMA 9/10 Pro		
Hardware Interface	USB *1, Support OTG	USB *1, Support OTG		
	UART*3	UART*2		
	I2C*5	I2C*3		
	SPI*5	SPI*2		
	ADC *2	ADC*1		
	GPIO*24	GPIO*21		
	SIM Card*2	SIM Card*3		
	SDIO*1+FF43:144	SDIO *1		
Antenna	Main antenna , Diversity antenna , GNSS Antenna , Wi-Fi/BT Antenna	Main antenna , Diversity antenna , GNSS Antenna , Wi-Fi/BT Antenna		
Certifications				
Certifications	CCC/CE/FCC/CTA*/PTCRB*/AT&T*	CCC/CE/ROHS/RCM/FCC*/Anatel*		
Recommended Applications				
Application Fields	Smart POS, Security Monitoring, Automotive Device, VR/AR, Information Collection equipment, Smart Robots, Smart Home, Intelligent Hardware, Industrial Smart Handhelds, Smart PAD, UAV, VR Camera, Full-view Camera, Multi-touch Device, Walkie-talkie, Smart Wearables, Vending Machines, Logistics Cabinet etc.			




MeiG Automotive Telematics Module Series






Product		MA800	Product		MA922/MA925
Product Picture			Product Picture		
Package	LGA 299pin		Package	LGA 524pin	
Dimension(mm)	37.5x33.0x3.0		Dimension(mm)	54.5x53.0x3.45	
Band(MHz)	-C	LTE-FDD: B1/B3/B5/B8 LTE-TDD: B38/B39/B40/B41 WCDMA: B1/B8 TD-SCDMA: B34/B39 CDMA&EVDO: BC0 GSM: 900/1800	Band(MHz)	-CN	5G FDD: N1/N3/N8/N28A 5G TDD: N41/N78/N79(N79 option) (N78 Support PC2) LTE-FDD: B1/B3/B5/B7/B8 LTE-TDD: B34/B38/B39/B40/B41 UMTS: B1/B8 GSM: 900/1800 C-V2X: B47
	-E	LTE-FDD: B1/B3/B5/B7/B8/B20 LTE-TDD: B40 WCDMA: B1/B5/B8 GSM: 900/1800		-EU	5G FDD: N1/N3/N8/N20/N28A/N71 5G TDD: N38/N40/N41/N78 (N78 Support PC2) LTE-FDD: B1/B3/B5/B7/B8/B20/B28A/B28B/B32R/B71 LTE-TDD: B38/B40/B41/B42 UMTS: B1/B3/B5/B8 GSM: 900/1800 C-V2X: B47
	-A	LTE-FDD: B2/B4/B5/B12/B13/B17/B25/B26 LTE-TDD: B41 WCDMA: B2/B4/B5 CDMA&EVDO: BC0/BC1 GSM: 850/1900		-NA	5G FDD: N2/N5/N12/N25/N66/N71 5G TDD: N78(N78 Support PC2) LTE-FDD: B2/B4/B5/B7/B12/B13/B14/B17/B25/B26/B29R/B30R/B66/B71 LTE-TDD: B38/B41 UMTS: B2/B4/B5 C-V2X: B47
	-SA	LTE-FDD: B2/B4/B5/B7/B8/B28 LTE-TDD: B40 WCDMA: B2/B5/B8 GSM: 850/900/1800/1900			
Weight	<8g		CPU	Internally Installed ARM Cortex-A55 Multicore CPU (~20K DMIPS)	
Working Temperature	-40°C~+85°C		Working Temperature	-40°C~+85°C	
Data Transmission			Data Transmission		
LTE Speed(Mbps)	LTE-FDD:150(DL)/50(UL) LTE-TDD:130(DL)/35(UL)		3GPP R16	MA922:5G NSA,SA (100 Mhz) MA925:5G NSA,SA (200 Mhz)	
DC-HSPA+Speed(Mbps)	42(DL)/5.76(UL)		NR Speed (bps)	NSA:Max. 2.4 Gbps (DL)/550 Mbps (UL) SA:Max. 2.0 Gbps (DL)/450 Mbps (UL)	
WCDMA Speed(Kbps)	384(DL)/384(UL)		LTE Speed (bps)	LTE-FDD:Max. 1.2 Gbps (DL)/100 Mbps (UL) LTE-TDD:Max. 1.0 Gbps (DL)/60 Mbps (UL)	
TD-SCDMA Speed(Mbps)	4.2(DL)/2.2(UL)		DC-HSPA+ Speed (bps)	HSDPA:Max.42 Mbps (DL) HSUPA: Max.5.76 Mbps (UL)	
EVDO RevB Speed(Mbps)	14.7(DL)/5.4(UL)		WCDMA Speed (bps)	Max.384 kbps (DL)/384 kbps (UL)	
EVDO RevASpeed(Mbps)	3.1(DL)/1.8(UL)		EDGE Speed (Kbps)	Max.296 kbps (DL)/236.8 kbps (UL)	
CDMA 1X Speed(Kbps)	153.6(DL)/153.6(UL)		GPRS Speed (Kbps)	Max.107 kbps (DL)/85.6 kbps (UL)	
EDGE Speed(Kbps)	236.8(DL)/236.8(UL)		V2X (bps)	C-V2X TDD up to 30 Mbps (Tx)/30 Mbps (Rx)	
GPRS Speed(Kbps)	85.6(DL)/85.6(UL)				
CSD	•				
Interface			Interface		
SIM	1.8V/3V		SIM	2	
UART	3		UART	4	
USB	•		USB	USB 3.1*1	
I2C	2		I2C	2	
Voice Simulation	—		PCIe	2	
PCM Voice	•		PCM Voice	1	
ADC	3		ADC	3	
GPIO	•		GPIO	15	
Antenna	ANT_PRI/ANT_DIV(optional)/GPS_ANT(optional)		Antenna	Primary Antenna *1 Diversity Antenna *1 MIMO Antenna *2 C-V2X Antenna*2 GNSS Antenna*1	
Special Function			Special Function		
DTMF	•		eCall/NG-eCall	•	
TTS	•		TCP/IP	•	
TCP/IP	•		PPE (RTK)	•	
FTP	•		Flash	4GB+4GB/8GB+8GB/16GB+16GB MCP(nand+lpddr4x)	
HTTP	•		QDR3	•	
RIL Driver	Android 4.4 Upper		OS	Linux	
NDIS	Windows XP/Vista/7/8/10		GNSS	•	
ECM	•		Firmware Update	•	
Gobinet	Linux 2.6 or later		Echo Cancellation	•	
GNSS	optional		Noise Suppression	•	
Firmware Update	USB/*FOTA		Short Message	•	
Electrical Parameter			Electrical Parameter		
Supply Voltage	3.3~4.2V, typ.3.8V		Supply Voltage	4.75V~5.25V,typ.5.0V	
Dormancy Power Consumption	<2mA		Dormancy Power Consumption	—	
Shutdown Leakage Current	100µA		Shutdown Leakage Current	—	
Certifications			Certifications		
Certifications	ROHS*/CCC*/CTA*/CE*/SRRC*/FCC*/GCF*		Certifications	SRRC*/CCC*/FCC*/CE*	
Recommended Applications			Recommended Applications		
Application Fields	It can be widely used in the fields of intelligent networked cars and in-vehicle BOX.		Application Fields	It can be widely used in the field of intelligent networked cars, in-vehicle BOX, V2X, RSU and so on.	

MeiG Automotive Cockpit Module Series





Product	MA951	SRM965	SRM935U
Product Picture			
Package	BGM970	SIP	LGA
Dimension(mm)	50.0*52.0*4.51	62.0*62.0*3.6	50.0*50.0*3.6
Band(MHz)	—	-C 5G-NR: N1/N3/N28/N41/N77/N78/N79 (NSA/SA)(N1,N28不支持NSA) LTE-FDD: B1/B3/B5/B8/B28 LTE-TDD: B34/B38/B39/B40/B41(196MHz) WCDMA: B1/B8 GSM: B3/B8	-C 5G-NR: N1/N3/N28/N41/N77/N78/N79(NSA/SA)(N1,N28不支持NSA) LTE-FDD: B1/B3/B5/B8/B28 LTE-TDD: B34/38/B39/B40/B41(196MHz) WCDMA: B1/B8 GSM: B3/B8
Weight	<23g	<22g	<18g
CPU	Kryo485, Prime@2.4G + 3xGold@2.0G +4xSilver@1.8G 105K DMIPS	1 x X3 @3.2 GHz, 2 x A715 @2.8GHz 2 x A710 @2.8 GHz ; 3 x A510 @2.0GHz 200K DIMPS	1xA78@2.7GHz + 3xA78@2.3GHz + 4xA55@2.1GHz 93 KDMIPS
GPU	Adreno640@700M 1100 GFLOPS	Adreno™ 740 @ 680MHz 2.15 TFLOPS	Mali-G57 486 GFLOPS
AI	NPU130, with ECC for ASIL-B 8TOPS	48 TOPS	IMG AX3596 8Tops
Working Temperature	-40°C~+85°C	Normal operating temperature: -30°C ~+75°C Extended operating temperature: -40°C~+85°C	Normal operating temperature: -30°C ~+75°C Extended operating temperature: -40°C~+85°C
Data Transmission			
Speed(bps)	—	3GPP Rel.16 5G NR sub-6 GHz 5G NR 256 QAM uplink/downlink in sub-6 GHz Rel.15 LTE multi-mode modem	3GPP Rel.15 5G NR sub-6 GHz 5G NR 256 QAM uplink/downlink in Sub-6 GHz Rel.15 LTE multi-mode modem
Interface			
Video Decode	4K120, H.265/H.264/VP9/VP8/MPEG-2	4K240/8K60- H.264/H.265/VP9	4K@30 H.264/H.265/VP9
Video Encode	4K60, H.265/H.264/VP8	4K120/8K30- H.264/H.265/VP9	4K@30 H.264/H.265
Audio	12ch LS/HS-I2S/PCM/TDM	4xHVX, NPU: 1xHTA	6 I2S(PCM) for audio codec connection
Display Support	3x4K or 4x2880x1080 or 2x4K + 1x2880x1080	2*4-lane MIPI DSI - 3840 × 2160@120 Hz, 3360 × 1600 @144 Hz , 1*DP (2x 4K60 or 1x 8K30)	DSI*2+DP QHD+@60fps/FHD+@120fps
Camera	4x4Lane-CSI	8 x 4-lane MIPI CSI 3 x ISP 2 × Lite ISP	4x CSI 64M(4in1) + 20M(UW) + 13M(T) + 2M
SIM	—	2	2
UART	4	4	5
Debug UART	1	•	•
USB	2	1xUSB3.1; Support OTG Type C	1xUSB3.1 + 1xUSB 2.0; Support OTG Type C
I2S	3	4	4
I2C	6	4	8
SDIO	2	1	1
PCIE	2	1	1
PCM	1	—	•
RGMII	1	—	—
ADC	3	2	2
SPI	2	3	3
GPIO	175	•	•
Antenna	—	Primary Antenna*4, GNSS Antenna*1, Wi-Fi&BT Antenna*2	Primary Antenna*4, Wi-Fi&BT Antenna*2
Special Function			
GNSS	—	•	•
Firmware Update	•	USB & FOTA	USB & FOTA
O S			
OS	Android Auto/Linux/QXN	Android	Android Auto/Linux/QXN
Electrical Parameter			
Supply Voltage	3.13V~3.46V typ.3.3V	3.5V~4.35V typ.3.8V	3.5V~4.35V typ.3.8V
Dormancy Power Consumption	—	6mA	3mA
Shutdown Leakage Current	—	150uA	150uA
Certifications			
Certifications	ACE-Q104	CCC*/SRRC*/CTA*/AEC-Q104*	CCC*/SRRC*/CTA*
Recommended Applications			
Application Fields	It can be widely used in the field of intelligent networked cars, in-vehicle BOX, V2X, RSU and so on.		



MeiG 4G LTE-A High-speed Module Series

Product	SLM828	SLM828G	SLM828M												
Product Picture															
Package	Mini PCIe	LGA	M.2												
Dimension(mm)	51.0*30.0*4.5mm	39.5x37.0x3.0	42.0x30.0x2.3												
Band(MHz)	<table border="1"> <tr> <td>-EU</td> <td>LTE-FDD:B1/B3/B5/B7/B8/B20/B28/B32 LTE-TDD:B38/B40/B41 WCDMA:B1/B3/B5/B8</td> </tr> <tr> <td>-NA</td> <td>LTE-FDD:B2/B4/B5/B7/B12/B13/B14/B17 B25/B26/B29/B30/B66/B71 WCDMA:B2/B4/B5</td> </tr> </table>	-EU	LTE-FDD:B1/B3/B5/B7/B8/B20/B28/B32 LTE-TDD:B38/B40/B41 WCDMA:B1/B3/B5/B8	-NA	LTE-FDD:B2/B4/B5/B7/B12/B13/B14/B17 B25/B26/B29/B30/B66/B71 WCDMA:B2/B4/B5	<table border="1"> <tr> <td>-EU</td> <td>LTE-FDD:B1/B3/B5/B7/B8/B20/B28/B32 LTE-TDD:B38/B40/B41 WCDMA:B1/B3/B5/B8</td> </tr> <tr> <td>-NA</td> <td>LTE-FDD:B2/B4/B5/B7/B12/B13/B14/B17 B25/B26/B29/B30/B66/B71 WCDMA:B2/B4/B5</td> </tr> </table>	-EU	LTE-FDD:B1/B3/B5/B7/B8/B20/B28/B32 LTE-TDD:B38/B40/B41 WCDMA:B1/B3/B5/B8	-NA	LTE-FDD:B2/B4/B5/B7/B12/B13/B14/B17 B25/B26/B29/B30/B66/B71 WCDMA:B2/B4/B5	<table border="1"> <tr> <td>-EU</td> <td>LTE-FDD:B1/B3/B5/B7/B8/B20/B28/B32/B38 LTE-TDD:B39/B40/B41/B42/B43 WCDMA:B1/B3/B5/B8</td> </tr> <tr> <td>-LA</td> <td>LTE-FDD:B2/B4/B5/B7/B8/B20/B28/B32/B66 LTE-TDD:B38/B39/B40/B41/B42/B43/B48 WCDMA:B2/B4/B5</td> </tr> </table>	-EU	LTE-FDD:B1/B3/B5/B7/B8/B20/B28/B32/B38 LTE-TDD:B39/B40/B41/B42/B43 WCDMA:B1/B3/B5/B8	-LA	LTE-FDD:B2/B4/B5/B7/B8/B20/B28/B32/B66 LTE-TDD:B38/B39/B40/B41/B42/B43/B48 WCDMA:B2/B4/B5
-EU	LTE-FDD:B1/B3/B5/B7/B8/B20/B28/B32 LTE-TDD:B38/B40/B41 WCDMA:B1/B3/B5/B8														
-NA	LTE-FDD:B2/B4/B5/B7/B12/B13/B14/B17 B25/B26/B29/B30/B66/B71 WCDMA:B2/B4/B5														
-EU	LTE-FDD:B1/B3/B5/B7/B8/B20/B28/B32 LTE-TDD:B38/B40/B41 WCDMA:B1/B3/B5/B8														
-NA	LTE-FDD:B2/B4/B5/B7/B12/B13/B14/B17 B25/B26/B29/B30/B66/B71 WCDMA:B2/B4/B5														
-EU	LTE-FDD:B1/B3/B5/B7/B8/B20/B28/B32/B38 LTE-TDD:B39/B40/B41/B42/B43 WCDMA:B1/B3/B5/B8														
-LA	LTE-FDD:B2/B4/B5/B7/B8/B20/B28/B32/B66 LTE-TDD:B38/B39/B40/B41/B42/B43/B48 WCDMA:B2/B4/B5														
Weight	<11g	<11g	<11g												
Working Temperature	-30°C~+75°C	-30°C~+75°C	-30°C~+75°C												
Data Transmission															
LTE Speed(Mbps)	LTE-FDD up to 600Mbps DL,100 Mbps UL support Cat.6/9/12	LTE-FDD up to 600Mbps DL,100 Mbps UL support Cat.6/9/12	LTE-FDD up to 600Mbps DL,100 Mbps UL support Cat.6/9/12												
DC-HSPA +Speed(Mbps)	—	—	—												
WCDMA Speed(Kbps)	•	•	•												
TD-SCDMA Speed(Mbps)	•	•	•												
EVDO RevB Speed(Mbps)	•	•	•												
EVDO RevASpeed(Mbps)	•	•	•												
CDMA 1X Speed(Kbps)	•	•	•												
EDGE Speed(Kbps)	•	•	•												
GPRS Speed(Kbps)	Max 85.6kbps(DL)/85.6kbps(UL)	Max 85.6kbps(DL)/85.6kbps(UL)	Max 85.6kbps(DL)/85.6kbps(UL)												
CSD	•	•	•												
Interface															
SIM	1.8V/3V	1.8V/3V	1.8V/3V												
UART	•	•	•												
USB	•	•	•												
I2C	•	•	•												
Voice Simulation	•	•	•												
PCM Voice	•	•	•												
ADC	•	•	•												
GPIO	•	•	•												
Antenna	Main Antenna, diversity Antenna, GPS Antenna	Main Antenna, diversity Antenna, MIMO*2, GPS Antenna	Main Antenna, diversity Antenna, MIMO*2, GPS Antenna												
Special Function															
DTMF	•	•	•												
TTS	•	•	•												
TCP/IP	•	•	•												
FTP	•	•	•												
HTTP	•	•	•												
RIL Driver	•	•	•												
NDIS	•	•	•												
ECM	•	•	•												
Gobinet	•	•	•												
GNSS	GPS/GLONASS	GPS/GLONASS	GPS/GLONASS												
Firmware Update	USB/*FOTA	USB/*FOTA	USB/*FOTA												
Electrical Parameter															
Supply Voltage	3.3V~4.2V, Typ3.6V	3.3V~4.2V, Typ. 3.6V	3.3V~4.2V, Typ. 3.6V												
Dormancy Power Consumption	<5mA	<5mA	<5mA												
Shutdown Leakage Current	50µA	50µA	50µA												
Certifications															
Certifications	*CE *FCC	*CE *FCC	*CE *FCC												
Recommended Applications															
Application Fields	Mobile Broadband, Industrial Routing, Automotive and Transportation, Green Energy, Wireless Payment, Smart Metering, Personal Tracking, Car-mounted DVR, Smart Industry, Medical Surveillance, Charging Pile, Video Surveillance etc.														




MeiG 4G M2M Module Series

Product	SLM720	SLM750/SLM750 Mini PCIe			
Product Picture					
Package	M.2	LCC : 80pin+other 64pin(SLM750)/52pin(SLM750 Mini PCIe)			
Dimension(mm)	42.0x30.0x2.3	32.0x29.0x2.8(SLM750)/51.0x30.0x4.8(SLM750 Mini PCIe)			
Band(MHz)	-CN	LTE-FDD:B1/B3/B5/B8 LTE-TDD:B34/B38/B39/B40/B41 WCDMA/HSPA+:B1/B5/B8	-C	LTE-FDD:B1/B3/B5/B8/B28(Optional) LTE-TDD:B38/B39/B40/B41 TD-SCDMA:B34/B39	WCDMA:B1/B8 EVDO&CDMA:BC0 GSM:900/1800
	-JP	LTE-FDD:B1/B3/B8/B18/B19/B26/B28 LTE-TDD:B41 WCDMA/HSPA+:B1/B8	-E	LTE-FDD:B1/B3/B5/B7/B8/B20 LTE-TDD:B40	WCDMA:B1/B5/B8 GSM:850/900/1800/1900
	-EU	LTE-FDD: B1/B3/B5/B7/B8/B20/B28 WCDMA/HSPA+:B1/B5/B8	-A	LTE-FDD:B2/B4/B5/B12/B13/B17/B25/26 LTE-TDD:B41 CDMA&EVDO:BC0/BC1	WCDMA:B2/B4/B5 GSM:850/1900
			-SA	LTE-FDD:B2/B4/B5/B7/B8/B28 LTE-TDD:B40	WCDMA:B2/B5/B8 GSM:850/900/1800/1900
			-AU	LTE-FDD:B1/B3/B5/B7/B8/B28 LTE-TDD:B40 CDMA&EVDO:BC0/BC1	WCDMA:B2/B4/B5 GSM:850/1900
			-J	LTE-FDD:B1/B3/B8/B18/B19/B26 LTE-TDD:B41	WCDMA:B1/B6/B8/B19
Weight	<6g	<5g(SLM750)/<11.5g(SLM750 Mini PCIe)			
Working Temperature	-30°C~+75°C	-40°C~+85°C			
Data Transmission					
LTE Speed(Mbps)	LTE-FDD (Cat.4): Max 150Mbps(DL)/50Mbps(UL) LTE-TDD (Cat.4): Max 130Mbps(DL)/35Mbps(UL)	LTE-FDD:150(DL)/50(UL) LTE-TDD:130(DL)/35(UL)			
DC-HSPA +Speed(Mbps)	—	42(DL)/5.76(UL)			
WCDMA Speed(Kbps)	•	384(DL)/384(UL)			
TD-SCDMA Speed(Mbps)	•	4.2(DL)/2.2(UL)			
EVDO RevB Speed(Mbps)	•	14.7(DL)/5.4(UL)			
EVDO RevASpeed(Mbps)	•	3.1(DL)/1.8(UL)			
CDMA 1X Speed(Kbps)	•	153.6(DL)/153.6(UL)			
EDGE Speed(Kbps)	•	236.8(DL)/236.8(UL)			
GPRS Speed(Kbps)	Max 85.6kbps(DL)/85.6kbps(UL)	85.6(DL)/85.6(UL)			
CSD	•	•			
Interface					
SIM	1.8V/3V	1.8V/3V			
UART	3xUART	•			
USB	•	•			
I2C	•	•			
Voice Simulation	•	Optional			
PCM Voice	•	•			
ADC	•	•			
GPIO	•	•			
Antenna	Main Antenna, diversity Antenna, GPS Antenna	ANT_PRI/ANT_DIV(Optional)/GPS_ANT(Optional)			
Special Function					
DTMF	•	•			
TTS	•	•			
TCP/IP	•	•			
FTP	•	•			
HTTP	•	•			
RIL Driver	•	Android 4.2/4.4/5.0/5.1/6.0/7.1/8.0			
NDIS	•	Windows XP/Vista/7/8/10			
ECM	•	•			
Gobinet	•	Linux 2.6 or later			
GNSS	GPS(Optional)	Optional			
Firmware Update	*FOTA	USB/*FOTA			
Electrical Parameter					
Supply Voltage	3.3V~4.2V, Typ3.8V	3.3~4.2V, typ.3.8V			
Dormancy Power Consumption	<5mA	<2mA			
Shutdown Leakage Current	50µA	100µA			
Certifications					
Certifications	CCC/SRRC/CTA/ROHS/CE/FCC/TELEC/JATE	AT&T/CCC/SRRC/CTA/CE/FCC/ROHS/KC/JATE/TELEC/ANATEL/NBTC/NOM/NCC/RCM/GCF/PTCRB/SoftBank/NTT DoCommo/KDDI			
Recommended Applications					
Application Fields	Mobile Broadband, Industrial Routing, Automotive and Transportation, Green Energy, Wireless Payment, Smart Metering, Personal Tracking, Car-mounted DVR, Smart Industry, Medical Surveillance, Charging Pile, Video Surveillance etc.				



MeiG 4G M2M Module Series

Product	SLM770A/SLM770A Mini PCIe		SLM770U/SLM770U Mini PCIe	
Product Picture				
Package	LCC +LGA 144pin(SLM770A) /52pin(SLM770A Mini PCIe)		LCC 80pin +LGA 64pin(SLM770U) /52pin(SLM770U Mini PCIe)	
Dimension(mm)	32.0×29.0×2.4mm(SLM770A) /51.0×30.0×5.2mm(SLM770A Mini PCIe)		32.0×29.0×2.4mm(SLM770U) /51.0×30.0×5.2mm(SLM770U Mini PCIe)	
Band(MHz)	-CA	LTE-FDD: B1/B3/B5/B8 LTE-TDD: B34/B38/B39/B40/B41 WCDMA: B1/B8 GSM: 900/1800	-CC	LTE-FDD: B1/B3/B5/B8 LTE-TDD: B34/B38/B39/B40/B41 WCDMA: B1/B8 GSM: 900/1800
	-CE*	LTE-FDD: B1/B3/B7/B8/B20/B28 LTE-TDD: B38/B40/B41 WCDMA: B1/B8 GSM: 900/1800	-CE	LTE-FDD: B1/B3/B7/B8/B20/B28 LTE-TDD: B38/B40/B41 WCDMA: B1/B5/B8 GSM: 900/1800
Weight	< 6g(SLM770A) /< 9g(SLM770A Mini PCIe)		< 6g(SLM770U) /< 9g(SLM770U Mini PCIe)	
Working Temperature	-40°C~+85°C		-40°C~+85°C	
Data Transmission				
LTE Speed(Mbps)	LTE-FDD up to 150Mbps DL, 50 Mbps UL Support Cat.4		LTE-FDD: 150Mbps DL, 50Mbps UL LTE-TDD: 130Mbps DL, 35Mbps UL	
DC-HSPA +Speed(Mbps)	42(DL)/5.76(UL)		42(DL)/5.76(UL)	
WCDMA Speed(Kbps)	384(DL)/384(UL)		384(DL)/384(UL)	
TD-SCDMA Speed(Mbps)	—		—	
EVDO RevB Speed(Mbps)	—		—	
EVDO RevASpeed(Mbps)	—		—	
CDMA 1X Speed(Kbps)	—		—	
EDGE Speed(Kbps)	236.8(DL)/236.8(UL)		236.8(DL)/236.8(UL)	
GPRS Speed(Kbps)	85.6(DL)/85.6(UL)		85.6(DL)/85.6(UL)	
CSD	•		•	
Interface				
SIM	1.8V/3V		1.8V/3V	
UART	2xUART		3xUART	
USB	•		•	
I2C	•		Optional	
Voice Simulation	•		•	
PCM Voice	•		•	
ADC	•		•	
GPIO	•		•	
Antenna	Main Antenna, diversity Antenna, GPS Antenna		Main Antenna, diversity Antenna, GPS Antenna	
Special Function				
DTMF	•		•	
TTS	•		•	
TCP/IP	•		•	
FTP	•		•	
HTTP	•		•	
RIL Driver	Android 4.2/4.4/5.0/5.1/6.0/7.1/8.0		Android 4.2/4.4/5.0/5.1/6.0/7.1/8.0	
NDIS	Windows XP/Vista/7/8/10		•	
ECM	•		•	
Gobinet	Linux 2.6 or later		Linux 2.6 or later	
GNSS	Optional		Optional	
Firmware Update	*FOTA		*FOTA	
Electrical Parameter				
Supply Voltage	3.3~4.2V, typ.3.8V		3.3~4.2V, typ.3.8V	
Dormancy Power Consumption	5mA		5mA	
Shutdown Leakage Current	20uA		20uA	
Certifications				
Certifications	CCC/SRRC/CTA/CE		CCC/SRRC/CTA/CE	
Recommended Applications				
Application Fields	Mobile Broadband, Industrial Routing, Automotive and Transportation, Green Energy, Wireless Payment, Smart Metering, Personal Tracking, Car-mounted DVR, Smart Industry, Medical Surveillance, Charging Pile, Video Surveillance etc.			





MeiG 4G LTE Cat.1 Module Series

Product	SLM320	SLM322	SLM326
Product Picture			
Package	LCC 80pin+LGA 64pin	LCC 76pin+LGA 16pin	LGA 120pin
Dimension(mm)	29.0x32.0x2.4	22.9x23.9x2.4	27.6x25.4x2.3
Band(MHz)	-C	-C	-C
	-E		-E*
	-LA*		-LA
Weight	<5g	<5g	<5g
Working Temperature	-30°C~75°C	-30°C~75°C	-30°C~+75°C
Data Transmission			
LTE Speed(Mbps)	LTE-FDD (Non-CA Cat.1):Max 10Mbps(DL)/5Mbps(UL) LTE-TDD (Non-CA Cat.1):Max 8Mbps(DL)/2Mbps(UL)	LTE-FDD (Non-CA Cat.1):Max 10Mbps(DL)/5Mbps(UL) LTE-TDD (Non-CA Cat.1):Max 8Mbps(DL)/2Mbps(UL)	LTE-FDD (Non-CA Cat.1):Max 10Mbps(DL)/5Mbps(UL) LTE-TDD (Non-CA Cat.1):Max 8Mbps(DL)/2Mbps(UL) GPRS:Max 85.6kbps(DL)/85.6kbps(UL)
DC-HSPA +Speed(Mbps)	—	—	—
WCDMA Speed(Kbps)	•	•	•
TD-SCDMA Speed(Mbps)	•	•	•
EVDO RevB Speed(Mbps)	•	•	•
EVDO RevASpeed(Mbps)	•	•	•
CDMA 1X Speed(Kbps)	•	•	•
EDGE Speed(Kbps)	•	•	•
GPRS Speed(Kbps)	Max 85.6kbps(DL)/85.6kbps(UL)	*	Max 85.6kbps(DL)/85.6kbps(UL)
CSD	•	•	•
Interface			
SIM	1.8V/3V	1.8V/3V	1.8V/3V
UART	3xUART	3xUART	3xUART
USB	•	•	•
I2C	•	•	•
Voice Simulation	Optional	Optional	Optional
PCM Voice	•	•	•
ADC	•	•	•
GPIO	•	•	•
Antenna	Main Antenna, BT/Wi-Fi Antenna, GPS Antenna (Optional)	Main Antenna, BT/Wi-Fi Antenna	Main Antenna, BT/Wi-Fi Antenna
Special Function			
DTMF	—	—	—
TTS	Optional	Optional	Optional
TCP/IP	•	•	•
FTP	•	•	•
HTTP	•	•	•
RIL Driver	•	•	•
NDIS	—	—	—
ECM	•	•	•
Gobinet	•	•	•
GNSS	Optional	No	—
Firmware Update	Optional	Optional	Optional
Electrical Parameter			
Supply Voltage	3.5V~4.2V, Typ3.8V	3.5V~4.2V, Typ3.8V	3.5V~4.2V, Typ3.8V
Dormancy Power Consumption	2mA	2mA	2mA
Shutdown Leakage Current	10uA	10uA	10uA
Certifications			
Certifications	CCC/SRRC/CTA/RoHS/FCC/RCM/NCC/PTCRB/CE/KC	*CE/**CCC/**CTA/**SRRC	CCC/**CTA/**SRRC/**CE*
Recommended Applications			
Application Fields	It can be widely used in mobile broadband, industrial routing, vehicle and transportation, wireless payment, green energy, smart meter, smart industry, medical monitoring, vehicle DVR, personal tracking, industrial tablet, charging pile, video surveillance and other fields.		




MeiG 4G LTE Cat.1 Module Series


Product	SLM336E	SLM336Q
Product Picture		
Package	LGA	LGA 126Pin
Dimension(mm)	19.9x23.6x2.4	19.9x23.6x2.4
Band(MHz)	-E LTE-FDD:B1/B3/B5/B7/B8/B20 LTE-TDD:B38/B40/B41 GSM:B2/B3/B5/B8	-E LTE-FDD:B1/B3/B5/B7/B8/B20/B28 -NA LTE-FDD:B2/B4/B5/B12/B13/B14/B66/B71*
Weight	<5g	<5g
Working Temperature	-30°C~75°C	-30°C~+75°C
Data Transmission		
LTE Speed(Mbps)	LTE-FDD (Non-CA Cat.1):Max 10Mbps(DL)/5Mbps(UL) LTE-TDD (Non-CA Cat.1):Max 8Mbps(DL)/2Mbps(UL)	LTE-FDD (Non-CA Cat.1): Max 10Mbps(DL)/5Mbps(UL)
DC-HSPA +Speed(Mbps)	—	—
WCDMA Speed(Kbps)	•	•
TD-SCDMA Speed(Mbps)	•	•
EVDO RevB Speed(Mbps)	•	•
EVDO RevASpeed(Mbps)	•	•
CDMA 1X Speed(Kbps)	•	•
EDGE Speed(Kbps)	•	•
GPRS Speed(Kbps)	*	•
CSD	•	•
Interface		
SIM	1.8V/3V	1.8V/3V
UART	3xUART	3xUART
USB	•	1*USB
I2C	•	3*IIC
Voice Simulation	Optional	Optional
PCM Voice	•	•
ADC	•	•
GPIO	•	•
Antenna	Main Antenna, BT/Wi-Fi Antenna	Main Antenna/GPS Antenna (Optional)
Special Function		
DTMF	—	—
TTS	Optional	•
TCP/IP	•	•
FTP	•	•
HTTP	•	•
RIL Driver	•	•
NDIS	—	—
ECM	•	•
Gobinet	•	•
GNSS	No	GPS
Firmware Update	Optional	* FOTA
Electrical Parameter		
Supply Voltage	3.5V~4.2V, Typ3.8V	3.5V~4.2V, Typ3.8V
Dormancy Power Consumption	2mA	6uA
Shutdown Leakage Current	10uA	1nA
Certifications		
Certifications	*CCC/*SRRC/*CTA/*CE	FCC/*CE*
Recommended Applications		
Application Fields	It can be widely used in mobile broadband, industrial routing, vehicle and transportation, wireless payment, green energy, smart meter, smart industry, medical monitoring, vehicle DVR, personal tracking, industrial tablet, charging pile, video surveillance and other fields.	

MeiG NB-IoT/Cat M Module Series

Product	SLM156		SLM156H		SLM156N		SLM130-G	
Product Picture								
Package	LCC+LGA(80pin)		LCC+LGA(80pin)		LGA(102pin)		LCC(44pin)+LGA(14pin)	
Dimension(mm)	20.0x21.0x2.3		20.0x21.0x2.3		23.6x19.9x2.3		17.7x15.8x2.0	
4G	LTE Cat NB2		LTE Cat NB2		LTE Cat NB2		LTE Cat NB2	
Band(MHz)	NB-IoT	B1/B2/B3/B4/B5/B8/B12 B13/B18/B19/B20/B25 B26/B28/B66/B71/B85	NB-IoT	B1/B2/B3/B4/B5/B8/B12 B13/B18/B19/B20/B25 B26/B28/B66/B71/B85	NB-IoT	B1/B2/B3/B4/B5/B8/B12 B13/B18/B19/B20/B25 B26/B28/B66/B71/B85	LTE Cat NB: B3/B5/B8/B20/B28	
	Cat M	B1/B2/B3/B4/B5/B8/B12 B13/B14/B18/B19/B20 B25/B26/B27/B28/B66 B85			Cat M	B1/B2/B3/B4/B5/B8/B12 B13/B14/B18/B19/B20 B25/B26/B27/B28/B66 B85		
	GPRS	850/900/1800/1900			Cat M	B1/B2/B3/B4/B5/B8/B12 B13/B14/B18/B19/B20 B25/B26/B27/B28/B66 B85		GPRS
Weight	<3g		<3g		<3g		<2g	
Working Temperature	-30°C~+75°C		-30°C~+75°C		-30°C~+75°C		-30°C~+75°C	
Data Transmission								
LTE Cat NB1 Speed(Mbps)	Cat M1: DL:588Kbps UL:1119Kbps Cat Nb2: DL:127Kbps UL:158.5Kbps		Cat M1: DL:588Kbps UL:1119Kbps Cat Nb2: DL:127Kbps UL:158.5Kbps		Cat M1: DL:588Kbps UL:1119Kbps Cat Nb2: DL:127Kbps UL:158.5Kbps		Single Toll (subcarrier 15KHz/3.75KHz) DL 25.2Kbps UL 15.625Kbps Multi Toll (subcarrier 15KHz) DL 25.2Kbps / UL 54Kbps	
LTE Cat NB2 Speed(Mbps)	—		—		—		DL 126.8Kbps/UL 158.6Kbps	
SMS	•		•		•		•	
Network Protocol	TCP/UDP/SSL/MQTT/COAP		TCP/UDP/SSL/MQTT/COAP		TCP/UDP/SSL/MQTT/COAP		TCP/UDP/SSL/MQTT/COAP	
Interface								
(U)SIM	USIM(1.8V)		USIM(1.8V)		USIM(1.8V)		USIM(3.0V/1.8V)	
UART	1 x UART		1 x UART		1 x UART		UART	
I2C	I2C		I2C		I2C		•	
ADC	1 x ADC		1 x ADC		1 x ADC		ADC	
GPIO	GPIO x n		GPIO x n		GPIO x n		GPIO	
RESET	RESET		RESET		RESET		RESET	
SPI	—		—		—		SPI	
PSM-EINT	PSM_EINT		PSM_EINT		PSM_EINT		PSM_EINT	
Aerial	Main /GNSS		Main /GNSS		Main /GNSS		1 x antenna interface	
Other	PCM		PCM		PCM		1 RI interface 1 network status indication interface	
Specific Function								
Open	—		—		—		•	
DFOTA	—		—		—		*	
Firmware upgrade	•		•		•		•	
RAI	—		—		—		•	
Base Station Positioning	•		•		•		•	
eSIM	—		—		—		*	
Electrical Specification								
Supply Voltage	3.3V~4.2V		3.3V~4.2V		3.3V~4.2V		2.2V~4.2V	
Consumption flow	Average current consumption in PSM mode: 1mA		Average current consumption in PSM mode: 1mA		Average current consumption in PSM mode: 1mA		Average current consumption in PSM mode: 0.8uA	
Certifications								
Certifications	SRRC/CTA/RoHS/CE/FCC		SRRC/CTA/RoHS/JATE/TELEC/DOCOMO		SRRC/CTA/RoHS/CE/FCC		SRRC*/CTA*/RoHS*/CE*	
Recommended Applications								
Application Fields	It can be widely used in gas meter, water meter, electric meter, smoke sensor, bike-sharing, street lamp, intelligent parking, agriculture, door lock, tracking, pet management, POS machine, positioning, asset management and other fields.							

MeiG NB-IoT/GNSS Module Series

Product	SLM130E	SLM130-G	SLM130-NA-S
Product Picture			
Package	LCC + LGA	LCC + LGA	LCC + LGA
Dimension(mm)	15.8*17.7*2.0	15.8*17.7*2.0	15.8*17.7*2.0
4G	LTE Cat.NB2	LTE Cat.NB2	LTE Cat.NB2
Band(MHz)	LTE Cat.NB: B1/B3/B5/B8/B20/B28	LTE Cat.NB: B3/B5/B8/B20/B28	LTE Cat.NB: B2/B4/B12/B13/B66/B5/ B26/B71
Weight	<2g	<2g	<2g
Working Temperature	-30°C~+75°C	-30°C~+75°C	-30°C~+75°C
Data Transmission			
LTE Cat NB1 Speed(Mbps)	Single Toll (subcarrier 15KHz/3.75KHz) DL 25.2Kbps UL 15.625Kbps Multi Toll (subcarrier 15KHz) DL 25.2Kbps / UL 54Kbps	Single Toll (subcarrier 15KHz/3.75KHz) DL 25.2Kbps UL 15.625Kbps Multi Toll (subcarrier 15KHz) DL 25.2Kbps / UL 54Kbps	Single Toll (subcarrier 15KHz/3.75KHz) DL 25.2Kbps UL 15.625Kbps Multi Toll (subcarrier 15KHz) DL 25.2Kbps / UL 54Kbps
LTE Cat NB2 Speed(Mbps)	DL 126.8Kbps/UL 158.6Kbps	DL 126.8Kbps/UL 158.6Kbps	DL 126.8Kbps/UL 158.6Kbps
SMS	•	•	•
Network Protocol	TCP/UDP/MQTT(s)/COAP/LwM2M/SSL	TCP/UDP/MQTT(s)/COAP/LwM2M/SSL	TCP/UDP/MQTT(s)/COAP/LwM2M/SSL
Interface			
(U)SIM	USIM(3.0V/1.8V)	USIM(3.0V/1.8V)	USIM(3.0V/1.8V)
UART	UART	UART	UART
I2C	•	•	•
ADC	ADC	ADC	ADC
GPIO	GPIO	GPIO	GPIO
RESET	RESET	RESET	RESET
SPI	SPI	SPI	SPI
PSM-EINT	PSM_EINT	PSM_EINT	PSM_EINT
Aerial	1 x antenna interface	1 x antenna interface	1 x antenna interface
Other	1 RI interface 1 network status indication interface	1 RI interface 1 network status indication interface	1 RI interface 1 network status indication interface
Specific Function			
Open	•	•	•
DFOTA	•	—	—
Firmware upgrade	•	•	•
RAI	•	•	•
Base Station Positioning	•	•	GNSS
eSIM	•	•	•
Electrical Specification			
Supply Voltage	2.2V~4.5V	2.2V~4.5V	2.0V~4.5V
Consumption flow	Average current consumption in PSM mode: 1mA	Average current consumption in PSM mode: 0.8mA	Average current consumption in PSM mode: 1.75mA
Certifications			
Certifications	CE*/SRRC/CTA/RoHS	CE/SRRC/CTA/RoHS	FCC/SRRC/CTA/RoHS
Recommended Applications			
Application Fields			

Product	SGM308
Product Picture	
Package	LGA
GNSS	GPS/Glonass/ Galileo/Beidou
Dimension(mm)	10.1x9.7x2.4
Weight	0.2g
Norm Temp	-30°C~+75°C
Storage	-40°C~+85°C
Main Features	
L1 rece (numbe	33 Tracking/99 Capture
L1 rec	•
A-GNSS	•
Sensiti (autom	-148
Sensit	-160
Sensit	-167
TTF (first positioning time) cold start	23.9s
TTF (first positioning time) Warm start	<35S
TTF (first positioning time) hot start	0.2s
Position accuracy	176.56m (95%) 54.07m (50%)
Speed accuracy	<0.1m/s
Maxim accur	<0.1m/s ²
Low no	•
Electrical parameters	
Supply	2.8V~4.3V
I/O volt	2.7V~2.9V
Power (captur	21mA (GPS) 29mA (GPS+Glonass)
Power (tracki	8mA (GPS+Glonass)/ 15mA (GPS) 22mA (GPS+Glonass)
Power (RTC t	7uA
Interface	
UART	•
IIC (NM	•
Recommended Applications	
Application Fields	And vehicle transportation, electronic dog, medical monitoring, agriculture and other fields.

MeiG Pi Developer Kit



MeiG Pi-QCS8550



MeiG Pi-QCS6490

MeiG Pi QCS8550

- 1 x X3 @3.2 GHz
- 4x A715/A710 @2.8 Ghz
- 3 x A510 @2.0 GHz
- AI: 48 Tops
- OS: Android 13/Linux 5.15
- Memory: 16+256GB /24+512GB
- Wi-Fi 7 / BT 5.3

MeiG Pi QCS6490

- 1 x A78@2.7GHz
- 3 x A78@2.4GHz
- 4 x A55@1.9GHz
- AI: 12Tops
- OS: Android 14/Linux 6.16
- Memory: 8+128GB /12+256GB
- Wi-Fi 6E/ BT 5.2

Functional interface

- 4 x USB-A3.0
- 1 x Type-C 3.0, Support DP
- 4 x MIPI CSI ,12M/48M
- 1 x HDMI-OUT, 1080P/30fps
- 1 x HDMI-IN, 4K/30fps
- 2 x CAN
- 1 x RS232
- 1 x RS485
- 2x RJ45:1000 Mbps/2.5Gbps
- 1 x MIPI DSI
- GPIOs: Support I2C, SPI, I2S

Replacement

- 1x 12V Power Adapter
- 1x Camera 12M
- 2 x Antenna
- 1 x Type-C Cable
- 1 x LCD 5 inch (1280*720)
- 1 x FAN



Qualcomm



High computing power



LLM



Linux/Android multi-system



Industrial interface



Multi camera access




Multi screen display



Multistream

MeiG Smart focuses on three aspects: AI applications, AI hardware, and AI deployment. Based on Qualcomm's IoT platform, it has developed the MeiG Pi series developer kits, including MeiG Pi-QCS8550 and MeiG Pi-QCS6490. These kits boast powerful AI capabilities with a maximum of 48 TOPS of AI computing power, supporting various AI algorithms. With a complete AI development toolchain, they enable rapid deployment of edge-side AI applications across multiple industries and scenarios, improving work efficiency, reducing costs, and helping enterprises quickly complete digital transformation in the AI era.

AI Development Toolchain



MEIG AI Development Tool

- Supports multiple high-performance platforms from MeIG Smart.
- Offers a variety of models and algorithms, covering different types of application scenarios.
- Open-source, including both the app and model capabilities, available for reference or direct use.
- Provides development documentation to help understand the app structure, code, and models.
- Offers video tutorials on algorithm conversion and integration.

	TensorFlow	TensorFlow Lite	PyTorch	mmet/Cognitive Toolkit/PaddlePaddle	
	.pb	.tflite	pt/.onnx	.onnx	
ML Runtime Frameworks and Application	Other ML Frameworks and Applications				
	Qualcomm® Neural Processing SDK	PyTorch Mobile	TF-Lite	ONNX RT	
Qualcomm® AI Engine Direct Backend Libraries	Qualcomm® AI Engine Direct API	Qualcomm® AI Engine Direct API	Qualcomm® AI Engine Direct API	Qualcomm® AI Engine Direct API	Qualcomm® AI Engine Direct API
	QIL	Kernels	HIP Core	HexNv2	HexNN-RTA
	NEON	OpenCL	MDL/HWY	HVI	RTA
Hardware IP Core	CPU	GPU	HIP	cDSP	RTA


High Computing Power AI Hardware Matrix

- AI computing power ranges from 12 TOPS to 80 TOPS.
- Various packaging options and functional interfaces.
- Validated with dozens of models across machine vision, speech/audio, natural language, and multimodal applications.
- Extensive experience in large-scale mass production.
- A comprehensive "model optimization - algorithm deployment - scenario implementation" ecosystem built in collaboration with ecosystem partners



MeiG Smart, in collaboration with its ecosystem partners, provides comprehensive technical support throughout the entire process—from model conversion, optimization, and quantization to model inference and deployment. This helps solve the "last mile" challenge of edge-side AI deployment. The company has successfully verified the operation of numerous models, including DeepSeek, Qwen, LLaMA-2, RedPajama, Yolov8, Inswapper, Hand Landmark, and many others across machine vision, speech/audio, natural language, and multimodal domains, with deployment support for dozens of large models.

5G Intelligent Cockpit Solution



System Platform

- Chip: Qualcomm 5G QCM8538 1 x X3 @3.2 GHz ; 2 x A715 @2.8GHz
2 x A710 @2.8 GHz ; 3 x A510 @2.0GHz 200K DIMPS
Qualcomm 5G QCM6490 1*GoldP@2.7GHz + 3*Gold@2.4GHz
+ 4*Silver@1.9GHz
- Memory: 4GB + 64GB/6GB + 128GB/8G + 128GB LPDDR4X uMCP
- Size: 47.0*48.0*3.0mm
- Package: LGA

Product Characteristics

- Android
- 5G network connection
- AI
- Multi-screen display
- Multi-camera access
- H.264/H.265 Hardware codec

Network Parameter

- Data Traffic: 5G/4G/3G/2G frequency band, support 5G Sub-6G
- Wireless connection: support Wi-Fi 2.4G/5G, ax-Ready
- Bluetooth: BT5.0, support BLE
- Global navigation satellite system: GPS/Beidou/Glonass/Galileo, support L1+L5



5G
network connection



Qualcomm chip



AI Smart



Android



Quick boot



Multi-camera
access



Multi-screen
display



Multi-stream

MeiG is the first to launch 5G smart module, which supports Android system and has 15Tops AI computing power. It provides mature SDK development packages. The module has been fully tested and meets the requirements of the ICV application scenario.

5G Industrial PDA Solution



System Platform

- Chip: Qualcomm 5G QCM6490 1*2.7GHz + 3*2.4GHz + 4*1.9GHz
Qualcomm 5G SM4350 PRO 2*A76 2.2Ghz +6*A55 1.9Ghz
Qualcomm 4G QCM4290 4*A73 2.0Ghz + 4*A53 1.8Ghz
- Memory: Up to 256GB UFS +8GB DDR5
- Whole machine Size: 162.0*76.0*19.0mm
- Screen Size: 5.5'-6.0'HD/FHD

Network Parameter

- Data Traffic: 5G/4G/3G/2G frequency band, support 5G Sub-6G & mmW
- Wireless connection: support Wi-Fi 2.4G/5G and Wi-Fi 6/6E
- Bluetooth: BT5.2, support BLE
- Global navigation satellite system: GPS/Beidou/Glonass/Galileo, support L1+L5



Qualcomm chip



IP67



FHD



13M PDAF



Android



Scan code



AT&T Certifications



GMS



NFC



5000mAh

MeiG adopted the Qualcomm platform to provide customized ODM solutions and services for customers. The product supports various wireless communication functions such as 4G/5G global frequency band, BT, GPS, Wi-Fi and NFC, also supports professional scanning engine like Zebra&Honeywell, it meets IP67 and 1.5m drop reliability requirements, and is widely used in logistics, express delivery, warehouse management, retail, hospitals and various information collection industries.

5G Industrial Panel Solution



Parameter Configuration

- Chip: Qualcomm 5G QCM6490 1*2.7GHz + 3*2.4GHz + 4*1.9GHz
- Operating system: Android
- Camera: 64M Back Camera, 8M Front Camera, front 8M FF
- Memory: 128GB UFS +8GB DDR5
- Battery capacity: 8000mA
- Screen size: 10.1" FHD (1920x1080)
- Radio frequency band configuration:
 - American radio frequency configuration:
 - 5G-NR: N2/N5/N12/N25/N30/N38/N41/N48/N66/N71/N77/N78
 - LTE-FDD: B2/B4/B5/B7/B12/B13/B14/B17/B25/B29/B30/B46/B66/B71
 - LTE-TDD: B38/B41/B42/B43/B48
 - WCDMA: B2/B4/B5
 - GSM: B2/B3/B5/B8
 - Eurasian RF configuration:
 - 5G-NR: N1/N3/N7/N8/N28/N38//N41/N77/N78/N79
 - LTE-FDD: B1/B2/B3/B5/B7/B8/B20/B26/B28
 - LTE-TDD: B38/39/B40/B41
 - TD-SCDMA: B34/39
 - WCDMA: B1/B3/B5/B8
 - GSM: B2/B3/B5/B8
- Support RoHS/CCC/FCC/CE/GCF/PTCRB compulsory certification, and AT&T/Verizon Operator certification
- Global navigation and positioning system GPS/GLONASS/NavIC/BeiDou/Galileo/QZSS and SBAS
- Wireless connection: support Wi-Fi 2.4G/5G/6E 2x2 MU-MIMO, BT5.2, support DBS



5G



Qualcomm chip



FHD



13M PDAF



Android



Wi-Fi 6E



AT&T authentication



BT5.2



IP67



8000mAh

MeiG Smart's 5G industrial panel solution is the industry's first design and development based on Qualcomm's QCM6490 5G platform. The solution meets MIL-MT810G standard and IP67 waterproof rating while complying with regulatory and certification standards from PTCRB/GCF as well as major carriers such as AT&T/Verizon. It supports global Sub-6G frequency bands and Wi-Fi 6E wireless standard to satisfy the needs of various high-speed application scenarios. The solution is widely used in logistics, warehousing, inventory management and other information/data collection industries.

5G FWA Solution




5G CPE SRT858M

- 5G NR Sub-6GHz
- Qualcomm X72+QFW7124
- Support Global Mainstream Frequencies
- Support Wi-Fi 7 802.11 a/b/g/n/ac/ax/be 2*2 MIMO, BE6400
- Support 2*1GE(2.5GEis Optional) +1*RJ11
- Support external antenna port
- Size: 180.0*100.0*100.0mm



5G CPE SRT858L

- 5G NR Sub-6GHz
- Qualcomm X62+WCN6856
- Support Global Mainstream Frequencies
- Support Wi-Fi 6 802.11 a/b/g/n/ac/ax 2*2 MIMO, 3.6Gbps
- Support 2*1GE(2.5GEis Optional) +1*RJ11
- Support external antenna port
- Size: 217.5*112.0*112.0mm



5G CPE SRT838I Pro

- 5G NR Sub-6GHz
- Qualcomm X62+WCN6856
- Support Global Mainstream Frequencies
- Support Wi-Fi 6 802.11 a/b/g/n/ac/ax 2*2MIMO AX1800
- Support 1*GE
- Speed 2.4Gbps
- Size: 160.0*72.0*53.0mm



5G CPE SRT838C

- 5G NR Sub-6GHz
- UNISOC V510+QCA2064
- Support Global Mainstream Frequencies
- Support Wi-Fi 6 802.11 a/b/g/n/ac/ax 2*2MIMO AX1800
- Support 1*GE
- Speed 2.4Gbps
- Size: 160.0*72.0*53.0mm



5G CPE SRT835

- 5G NR Sub-6GHz
- Qualcomm X35+WCN6856
- Support Global Mainstream Frequency Band, SA only
- Support Wi-Fi 6 802.11 a/b/g/n/ac/ax
- 2*2MIMO AX1800
- Support 4*1GE+1RJ11
- Size: 295.0*168.0*52.0mm



5G mmWave Outdoor Unit

- Qualcomm X55/X62/X65
- 5G NR Sub-6GHz & mmWave
- QTM527
- IP65
- POE
- 2.5/5 Gigabit LAN
- Size: 186.0*111.0*35.0mm



5G Sub-6GHz Outdoor Unit

- Qualcomm X55/X62/X65
- Up to 2.1Gbps rate
- IP65
- POE
- 1/2.5 Gigabit LAN
- Size: 186.0*111.0*35.0mm



5G BOX SRT830

- Qualcomm X55
- 5G NR Sub-6GHz
- Support Wi-Fi 6
- 802.11 a/b/g/ac/ax
- 1 Gigabit LAN
- DC 12V/1.5A
- Size: 125.0*78.0*27.0mm



5G BOX SRT831

- Qualcomm X55
- 5G NR Sub-6GHz & mmWave
- QTM525
- RS232/485
- 5 Gigabit LAN
- DC 12V/24A
- Size: 126.0*71.0*27.0mm

5G FWA Solution




5G MiFi SRT873

- 5G NR Sub-6GHz
- Qualcomm X55+QCA6391
- Support Global Mainstream Frequencies
- Support Wi-Fi 6 2*2 MIMO
- Speed 4.1Gbps
- Lithium Battery 5000mAh, long standby
- 2.4 inch touch screen
- Size: 130.0*70.0*19.5mm



5G MiFi SRT873S

- 5G NR Sub-6GHz
- Qualcomm X55+QCA6391
- Support Global Mainstream Frequencies
- Speed 4.1Gbps
- Lithium Battery 3600mAh, Super long standby
- Support Wi-Fi 6 2*2 MIMO
- Size: 130.0*70.0*19.5mm



5G MiFi SRT875

- 5G NR Sub-6GHz
- Qualcomm X62+WCN6856
- Support Global Mainstream Frequencies
- Support Wi-Fi 6 2*2 MIMO DBDC AX3000
- Speed 3.6Gbps
- Lithium Battery 5000mAh, Super long standby
- Band Steering
- Size: 133.5*71.0*17.0mm



5G MiFi SRT878


- 5G NR Sub-6GHz
- Qualcomm X72+WCN7851
- Support Global Mainstream Frequencies
- Support Wi-Fi 7 802.11 a/b/g/n/ac/ax/be
- 2*2MIMO BE3600
- 5000mAh 2.4 Touch
- Size: 140.0*74.0*19.0mm



5G MiFi SRT876L

- 5G RedCap
- Qualcomm X35+WCN6856
- Support Global Mainstream Frequency Band
- Support Wi-Fi 6 802.11 a/b/g/n/ac/ax 2*2MIMO AX1800
- LCD: 1.44Inch Screen
- Battery: 3000mAh
- Working Hours: 7h
- Size: 130.0*70.0*19.5mm

Our Partners



Livestreaming Box Solution



System platform

- Processor: eight nuclear 2.0-2.8GHz, high-pass chip SDM660/QCM6490*/QCS8250*
- Android 9.0/10.0/11.0, custom motherboard+Smart Module SLM900/SRM930*/SNM951* (flexible configuration)

Product characteristics

- Support 2560 * 1600 @ 60fps/FHD+1080 * 2520 @ 60fps 4K video recording and playing
- Eight nuclear's high-performance CPU, configurable with large-capacity battery, supports Type-c charging and broadcasting, and long-time live broadcast is more stable.
- Synchronous video loop-out: multi-channel mixing and 4-channel camera interface cameras, SLR, UAV, camera, DV, PC and other video acquisition devices.
- Rich interface support: including LCM, touch screen, camera, microphone, speaker, UART interface, USB interface, I2C interface, SPI interface, etc. Support voice, multi-platform live broadcast by camera, multi-station switching, video guide and so on. Support active and passive audio access, microphone, local video, HDMI and USB channels, and lock one or more channels of mixing and control.
- A variety of network standards: LTE-TDD/LTE-FDD/WCDMA/EVDO/TD-SCDMA/CDMA/GSM, and a broadband intelligent wireless communication module integrating GNSS and 2.4&5G Wi-Fi.



Qualcomm
Eight nuclear



4K
Video



Support
2560*1600@60fps



Android 9.0/10.0/11.0
MeiG Depth customization



Multichannel seeding



4-Camera
Shooting



All Netcom



USB
Type-C interface

MeiG Smart's MC539 is a customized industry solution for live streaming device with full network coverage (2G/3G/4G/5G). The solution is a customized PCB (can be designed according to client's ID and preferences) developed with MeiG's smart modules SLM900/SRM930*/SNR951, enabling our partners to set up live broadcast studios easily and helping to satisfy the needs of multiple and diverse application scenarios required for live streaming.

Edge AI BOX Solution



System Platform

- Based on Qualcomm QCM6490/QCS8250/SM8475/QCS8550 Platform
- Internally Installed MeiG 5G High computing power AI module SNM930, SNM950, SNM960, SNM970

Product Characteristics

- 14Tops~48Tops High computing power and support for one-stop edge device management
- Integrated thermal design for continuous operation without compromising performance
- Supports Wi-Fi 6E for faster and more stable wireless connection
- Rich extended interfaces, support rapid deployment in different scenarios
- Differ from traditional surveillance camera, support external mipi camera, small size

AI Big Model Support Manufacturer:



Qualcomm chip



High Computing Power AI
14Tops~48Tops



BT5.2



Android
MeiG Deep customization



Wi-Fi6E



Rich interface



All netcom



Ultra Small Volume

MeiG Smart's 5G high-computing-power AI modules SNM930, SNM950, SNM960, SNM970 based on Qualcomm's QCM6490, QCS8250, SM8475, and QCS8550 platforms have launched an AI edge computing box solution with a lightweight edge-end technology engine, which can be accessed to the network camera in order to provide the video algorithm analysis capability, and has an arithmetic power of up to Around 14Tops~48Tops, supporting Wi-Fi 6E, BT5.2 and Android, the products can be widely used in unmanned vending systems, VR Camera, intelligent robots, video surveillance, security monitoring, intelligent information collection devices, live broadcast terminals and other products.

Cash register Solution



System Platform

- Processor: Qualcomm Snapdragon Quad-Core/Octa-Core

Display

- Screen interface: support MIPI, EDP, LVDS, HDMI
- Screen size: 15 inches/10 inches/7 inches

Network Parameters

- Data Traffic: 4G/3G/2G global frequency band
- Wireless connection: 2.4G/5G supports IEEE 802.11 a/b/g/n/ac
- Bluetooth: BT4.1, support BLE



Qualcomm
Quad-Core/Octa-Core



Dual screen
abnormal display
abnormal touch



FHD-1920X1080



Android



USB Type A*4



Micro USB*1



Power interface



RJ45



RJ12-Money box mouth



RJ11-232 Serial port



UART*3



Headset

MeiG Smart's cash register solution is the industry's first industrial motherboard designed with Qualcomm Snapdragon octa-core CPU, supporting 4-port USB, RJ45, RJ12, RJ11, Micro-USB, earphone and other interfaces. With the use of structured-light camera, it supports biometric technology in live facial recognition which can be applied to financial scenarios such as face recognition payment. It also supports eSIM technology which opens up a new era of virtual and interoperable cellular IoT applications. The solution is suitable for industries such as restaurant chains, unmanned supermarkets and convenience stores, providing comprehensive features such as self-checkout, front-desk checkout, self-ordering, online ordering, cash register management, membership management, inventory management, etc.

Smart POS Solution



System Platform

- Processor: Qualcomm QCM2150/QCM2290/UNISOC SL8541E
- Operating System: Android

Display

- Screen size: 5 inches

Network Parameters

- Data Traffic: 4G/3G/2G global frequency band
- Wireless connection: 2.4G/5G supports IEEE 802.11 a/b/g/n/ac
- Bluetooth: BT4.1, support BLE



Printer



Scan code



NFC



National secret algorithm



IC Card



Magnetic stripe card



720P



5M Camera

MeiG Smart's cash register solution is the industry's first industrial motherboard designed with Qualcomm Snapdragon octa-core CPU, supporting 4-port USB, RJ45, RJ12, RJ11, Micro-USB, earphone and other interfaces. With the use of structured-light camera, it supports biometric technology in live facial recognition which can be applied to financial scenarios such as face recognition payment. It also supports eSIM technology which opens up a new era of virtual and interoperable cellular IoT applications. The solution is suitable for industries such as restaurant chains, unmanned supermarkets and convenience stores, providing comprehensive features such as self-checkout, front-desk checkout, self-ordering, online ordering, cash register management, membership management, inventory management, etc.

4G CPE Solution

4G
CPE

6 Key Features



4G to WAN, enjoy high speed network



4G to Wi-Fi, wireless connection, fast and convenient



Wi-Fi dual-band 2.4G & 5GHz



SIM Card plug and play



WAN Port(s)+LAN Port(s) Combination



Voice: CS Voice VIOP/VoLTE



4G CPE SLT866H



4G CPE SLT868Q



4G CPE SLT866



4G CPE SLT818B

4G Platform:

- ASR 1803 Cat.4
- ASR 1826 Cat.6
- Qualcomm 9x07 Cat.4
- Qualcomm SDX12 Cat.6 up to Cat.12 (Support CA)
- Qualcomm 9x50 Cat.6 up to Cat.16 (Support CA)
- Qualcomm SDX20 Cat.18 (Support CA)

Wi-Fi Platform:

- MTK MT7621
- Qualcomm 6174 2.4GHz & 5GHz
- Realtek 8192 2.4GHz
- Qualcomm IPQ4019 Hard AP & Cost efficiency
- Qualcomm WCN6856 Wi-Fi 6E
- Qualcomm WCN7851 Wi-Fi 7

4G CPE Solution

4G
CPE



4G CPE SLT728



4G CPE SLT719



4G CPE SLT711



4G CPE SLT818H

Frequencies:

4G modules can be changed to meet the frequency demands of main global carriers. (LTE-FDD, LTE-TDD, WCDMA, EVDO & CDMA, GSM)

Usage Scenarios:

Indoor Wi-Fi hotspot, home gateway & voice call, outdoor networking, monitoring camera equipment, no fixed line area, party, laptops, registers, etc.



4G ODU SLT869



4G IDU SNT151

4G MiFi/Dongle Solution



4G MiFi SLT776

- Chip: Qualcomm MDM9x07 Cat.4
- Wi-Fi: 2.4G, Wi-Fi 1*1/2*2 (optional) 802.11 b/g/n
- Battery: Li-ion Battery 2200mAh
- Band: Support global frequency band
- Working Hours: 7h(2200mAh)/10h(3000mAh)
- Standby Time: 450h(2200mAh)/600h(3000mAh)
- Optional Configuration: Screen optional
- Size: 99.0*60.0*14.0mm



4G MiFi SLT778

- Chip: Qualcomm MDM9x07 Cat.4
- Wi-Fi: 2.4G, Wi-Fi 1*1/2*2 (optional) 802.11 b/g/n
- Battery: Li-ion Battery 2200mAh
- Band: Support global frequency band
- Working Hours: 7h(2200mAh)/10h(3000mAh)
- Standby Time: 450h(2200mAh)/600h(3000mAh)
- Optional Configuration: Screen optional
- Size: 99.0*60.0*14.0mm



4G MiFi SLT879EL

- Chip: Qualcomm SDX12 Cat.6
- Support global mainstream frequency band
- Wi-Fi: 802.11 a/b/g/n/ac
- LCD: 3*LED
- Battery: 2200mAh
- Working Hours: 7h
- Size: 112.0*65.0*17.0mm



4G MiFi SLT879EH

- Chip: Qualcomm SDX12 Cat.6
- Support global mainstream frequency band
- Wi-Fi: 802.11 a/b/g/n/ac
- LCD: 1.44Inch Screen
- Battery: 3000mAh
- Working Hours: 7h
- Size: 112.0*65.0*17.0mm



4G MiFi MT504

- Chip: UNISOC V8310 Cat.4
- Wi-Fi: 802.11 b/g/n,channel 1~13
- Battery: Lithium battery 2200mAh
- Band: Support global frequency band
- Working Hours: 7h(2200mAh)
- Standby Time: 450h(2200mAh)
- Optional Configuration: Lithium battery 3000mAh, adapter
- Size: 99.0*60.0*14.0mm



4G USB Dongle MT548

- Chip: UNISOC V8310 Cat.4
- Wi-Fi: 802.11 b/g/n,channel 1~13
- Port: Type C port
- Band: Support global frequency band
- Optional Configuration: Type A male connector to Type C male connector
- Size: 75.0*27.0*11.0mm

Find you everywhere!

Tracker



Tracker SLT181-S1(9207)



Tracker SLT181-S2(9207)



Tracker SLT188(9205)



Tracker MA500(9X07)

Qualcomm 9207:

- LTE-FDD, LTE-TDD, DC-HSPA, TD-SCDMA, GSM
- Wi-Fi 802.11ac
- BLE
- GPS, Glonass, Beidou, Galileo

Short-distance travel

- Scooter-sharing, Bike-sharing
- Private automobiles for short distance travel
- CAN Battery Global Band

Qualcomm 9205:

- NB-IoT Tracker; NB/Cat M/EGPRS ; GPS /LBS/Wi-Fi Position (2.4G Only) ; Lower power & smaller footprint;
- Additional and improved capabilities-Rel.14 LTE Cat.NB2-Rel.14 LTE Cat.M1, GNSS and security enhancements

Precise location tracking

- Precision location tracking
- Tracking history memory
- Data collection
- Motion detected
- CAN Battery Global Band
- Remote Control
- Vehicle tracking
- Electronic fence alarm
- FOTA

Various network systems: 4G, 3G, NB, GSM.

Various Product types: vehicle-mounted industry products and consumer products.

Care

- Elder /Child/Pet care
- SOS for help
- Motion/period/find Mode
- Activity monitoring

Interface

- 2xRS232
- 1xSpeaker
- 1xRS485
- 1xACC Detect
- 1xCAN
- 2xLED

Safety

- Accurate indoor and outdoor positioning
- Lost and retrieved
- Geofencing and alert notification

Product Key feature

Type	GPS Tracker
Mode	NB-IoT/Cat-M/GSM
Frequency	Global
GNSS	Qualcomm integrated ,low power consumption
Bluetooth	BLE
WiFi	2.4GHz, 802.11b/g/n, provide A-GPS function
LED UI	Breathing light
Mic & Speaker	Support Mic & Speaker
sensor	A+G sensor, Various sensors (Temperature/Humidity/Pressure)
Water proof	Waterproof & dustproof design

Application scenario:



5G


5G+AIoT

5G, AI and IoT technologies will become the core technologies of the intelligent world. MeiG focuses on R&D, production and sales of 5G, AI and IoT technologies and products, Continues to lead the development of 5G+AIoT smart module with high computing power.



1000+ R&D Personnel

3 R&D centers in Shenzhen, Shanghai and Xi'an, with R&D driving technology development Focusing on core application fields such as IoT universal connection, ICV, FWA and PC Set up R&D and sales branches in Japan, Germany, the United States, Singapore, etc. To accelerate the pace of globalization



Main Channels of Product Application

The intelligent connected vehicle field with new energy vehicles as the core
The universal connection field of Internet of Things represented by new retail and handheld PDA.
5G and 4G Fixed Wireless Access Field
Innovative development fields such as cloud computing and new energy



Global Sales Map

Attach equal importance to domestic and overseas market,
Successfully provide technical services such as IoT technology development and IoT core link hardware and software platform for more than 100 countries and regions around the world,
The market share is in the world's leading level.

MeiG Smart Technology Co.,Ltd

Add: 32/F, Building B, Shenzhen International Innovation Center, No.1006 Shennan Avenue, Futian District, Shenzhen, China
Tel: +86-755-8321 8588 Fax: +86-755-8321 9788
E-mail: sales_os@meigsmart.com Web: www.meigsmart.com



MeiG Smart Official Wechat QR Code



MeiG Smart Wireless Solutions